



4011




4011-0-15-XX-30-XX-04-0
Press-fit in 1,45 mounting hole

1801




1801-0-15-XX-30-XX-04-0
Press-fit in 1,45 mounting hole
Shell is Ph. Br. Alloy 544 (B2)

1001




1001-0-15-XX-3X-XX-04-0
Press-fit in 1,45 mounting hole

0156




0156-0-18-XX-30-XX-04-0
Self-retention socket pin 0,97-1,09 hole prior to soldering

0255




0255-0-15-XX-30-XX-04-0
Solder mount in 0,56 min. mounting hole

1109




1109-0-15-XX-30-XX-04-0
Hex press-fit in 1,45 plated thru hole

3013




3013-0-15-XX-32-XX-04-0
Press-fit in 1,45 mounting hole

0134



0134-0-15-XX-3X-XX-04-0
Press-fit in 1,45 mounting hole


0132/0135



013X-0-15-XX-30-XX-04-0
Press-fit in 1,45 mounting hole

Basic Part Number	Length A
0132-0	6,93
0135-0	4,65

0133/0147



01XX-0-15-XX-30-XX-04-0
Press-fit in 1,5 mounting hole

Basic Part Number	Length A
0133-0	9,7
0147-0	14,3

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - X - 1X - XX - XX - XX - 04 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08 μ m TIN/LEAD OVER NICKEL
- 80 5,08 μ m TIN OVER NICKEL (RoHS)
- 15 0,25 μ m GOLD OVER NICKEL (RoHS)



SPECIFY CONTACT FINISH:

- 02 2,54 μ m TIN/LEAD OVER NICKEL
- 84 2,54 μ m TIN OVER NICKEL (RoHS)
- 27 0,76 μ m GOLD OVER NICKEL (RoHS)

SELECT CONTACT

#30 or #32 CONTACT (DATA ON PAGES 218 & 219)