

OTTA 6-T



Terminal width 11

(IEC) flexible	I	U
[mm ²] stranded AWG	[A]	[V]

Connection data 0.1-6 26-10 41 800 *

Cable lug connection M4 max. external ø 9.6 mm

* The nominal voltage applies to insulated cable lugs.



Description	Color	Type	Order No.	Pcs. Pkt.
Terminal block , with universal foot with cable lug connection M4	gray	OTTA 6-T	07 90 44 6	50
Terminal block , as above, however, 4 mm Ø test socket screws	gray	OTTA 6-T-P/P	07 90 46 2	50

Accessories

(1) End cover	gray 	D-OTTA 6-T	07 90 45 9	50
(2) Insertion bridge , divisible, fully insulated,	3-pos. 	EB 3-OTTA 6	$I_{max.}$: 41 A 30 26 03 6	10
	4-pos.	EB 4-OTTA 6	41 A 30 26 04 9	10
	7-pos.	EB 7-OTTA 6	41 A 30 26 05 2	10
	10-pos.	EB 10-OTTA 6	41 A 07 90 42 0	10
(5) Zack strip , 10-section	white	ZB 10 (see info)		
(6) Screwdriver		SZS 1,0 x 6,5	12 05 07 9	10

Technical data

Dimensions

Width / length / end cover width	[mm]	11 / 69 / 1.5
Height (NS 35:7.5 / NS 35:15 / NS 32)	[mm]	52 / 59.5 / 57

Technical data in accordance with IEC/ DIN VDE

Maximum load current / cross section	[A] / [mm ²]	41 / 6
Max. cross section with insertion bridge (solid / stranded)	[mm ²]	6 / 6
Rated surge voltage / contamination class	[kV] / –	8 / 3
Surge voltage category / insulation material group	– / –	III / I

group

Ring cable lugs acc. to DIN 46234/46237

Terminal bolt / hole diameter / width	– / [mm] / [mm]	M 4 / 4.3 / max. 9.6 ø
---------------------------------------	-----------------	------------------------

Torque	[Nm]	1.5 - 1.8
--------	------	-----------

Color code		red/ blue / yellow
------------	--	--------------------

Disconnect slide

Thread / torque	– / [Nm]	M 4 / 1.5 - 1.8
-----------------	----------	-----------------

Insulation material		PA
---------------------	--	----

Inflammability class acc. to UL 94		V2
------------------------------------	--	----

Temperature indices RTI / Ti		125 / 100
------------------------------	--	-----------

Approval data (UL and CSA)

Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A]	600 / 30 / –
---	---------------	--------------

	CSA: [V] / [A] / AWG	600 / 25 / 22 - 10
--	----------------------	--------------------

Block diagram