


## TSD21DDGPC Product Details

[Live Product Chat](#)



**TSD21DDGPC**  
(1437579-5)

TE Internal Number: 1437579-5

[Active](#)

### Slide Switches

[Not EU RoHS or ELV Compliant \(Find RoHS Compliant Alternates\)](#)

#### Product Highlights:

- 2 Positions
- Single Pole - Double Throw Configuration (Pole-Throw)
- Actuator Style = Extended Dual, Top
- Actuator Color = Black
- TSS Series

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) | 
 [Request Sample](#) | 
 [Find Similar Products](#) | 
 [Buy Product](#)

### Documentation & Additional Information

<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">ALCOSWITCH PRODUCTS</a> (PDF, English)</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>
---	--

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Number of Positions</a> = 2</li> <li>• Configuration (Pole-Throw) = Single Pole - Double Throw</li> <li>• Actuator Style = Extended Dual, Top</li> <li>• Mount Angle = Vertical</li> <li>• Terminal Configuration = Standard</li> <li>• Termination Type = PC</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Contact Rating = 0.4 VA max @ 20 VDC or peak AC</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• Actuator Color = Black</li> <li>• Series = TSS</li> <li>• Mount Style = Through-Hole</li> <li>• PCB Tail Length (mm [in]) = 3.30 [0.130]</li> <li>• Actuator Material = Polyester</li> <li>• Flammability Rating = UL 94V-0</li> <li>• Length (mm [in]) = 10.20 [0.402]</li> <li>• Width (mm [in]) = 9.14 [0.360]</li> </ul>	<p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• Contact Plating = Gold</li> <li>• Contact Base Material = Copper</li> </ul> <p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• Operating Function = On None On</li> <li>• Number of Actuators = Dual</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> </ul> <p><b>Identification Marking:</b></p> <ul style="list-style-type: none"> <li>• Stamped Marking = With</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Alcoswitch</li> </ul>
---	---

#### Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

#### Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

#### Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)