AMPROBE°

Data Sheet

WT-20 Conductivity / TDS Pen-Type Water Quality Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy to use, one touch water management testers. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Dual LCD display with conductivity or TDS and temperature (selectable C and F)
- Adjustable TDS factor from 0.4 to 1.0
- Waterproof and dustproof IP65
- Convenient to use membrane keypad
- Quick response and easy to calibrate
- Auto power off
- Data hold
- Pen size, easy to fit in pocket.
- Low battery indicator
- Auto power off disable
- Easy one-touch multi point calibration



No hassle warranty

No waiting.





(note: \$500 MSLP limit)



WT-20 Conductivity / TDS Pen-Type Water Quality Meter

Data Sheet

Specifications

Weight	Approx. 56g (0.12 lb)	
Dimension	165 x 35 x 32mm (6.5 x 1.4 x 1.3 in)	
Calibration	2 point (Calibration range is ± 30% of factory default parameter)	
Power Requirements	4x 1.5V batteries (Type A76 or LR44)	
Normalization Temperature	20°C or 25°C (68°F or 77°F)	
Temperature Coefficient	0~4.0% per degree C	
Temperature Compensation	0°C to 50°C (32°F to 122°F)	
Operating Temperature	0°C to 50°C (32°F to 122°F)	
Calibration Standard Range	(0.2~1)* full scale	
Accuracy	±1% Full Scale ±1 dgt	
Resolution	1 uS or 0.01mS or 0.01ppt or 1ppm	
TDS Range	0~1999 ppm / 0~19.99 ppt	
Conductivity	0~1999 uS / 0~19.99 mS	

Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com

Everett, WA 98203 Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved. 7/2009 3520488 Rev A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AMPROBE: WT-20