

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**


The **MRF448** is Designed for  
High Linearity Class AB HF Power Amplifier  
Applications up to 30 MHz.

**FEATURES:**

- $P_E = 14$  dB Typical at 220 W/30 MHz
- $IMD_3 = -32$  dBc Typ. at 220 W(PEP)
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

$I_C$	16 A
$V_{CB0}$	100 V
$V_{CEO}$	50 V
$V_{EBO}$	4.0 V
$P_{DISS}$	290 W @ $T_C = 25$ °C
$T_J$	-65 °C to +200 °C
$T_{STG}$	-65 °C to +150 °C
$\theta_{JC}$	0.6 °C/W

**PACKAGE STYLE .500 4L FLG**


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B		.125 / 3.18
C	.245 / 6.22	.255 / 6.48
D	.720 / 18.28	.730 / 18.54
E		.125 / 3.18
F	.970 / 24.64	.980 / 24.89
G	.495 / 12.57	.505 / 12.83
H	.003 / 0.08	.007 / 0.18
I	.090 / 2.29	.110 / 2.79
J	.150 / 3.81	.175 / 4.45
K		.280 / 7.11
L	.980 / 24.89	1.050 / 26.67

**ORDER CODE: ASI10866**
**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
$BV_{CB0}$	$I_C = 100$ mA	100			V
$BV_{CEO}$	$I_C = 200$ mA	50			V
$BV_{EBO}$	$I_E = 10$ mA	4.0			V
$I_{CEO}$	$V_{CE} = 30$ V			5	mA
$I_{CES}$	$V_{CE} = 50$ V			10	mA
$h_{FE}$	$V_{CE} = 10$ V $I_C = 5.0$ A	10			---
$C_{ob}$	$V_{CB} = 50$ V $f = 1.0$ MHz		350	450	pF
$G_P$	$V_{CE} = 50$ V $I_{CQ} = 250$ mA $P_{OUT} = 250$ W(CW)	12	65		dB
$\eta_C$					%
$IMD$	$V_{CE} = 50$ V $I_{CQ} = 250$ mA $P_{OUT} = 250$ W(PEP)		-33	-30	dB
$\eta_C$			45		%

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advanced Semiconductor, Inc.:](#)

[MRF448](#)