

7022ACT Product Details



7022ACT
(1423162-6)

TE Internal Number: 1423162-6

Active

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- 7000 Electropneumatic Timing - Industrial Series
- Input Voltage = 110 VAC, 120 VAC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 240 VAC
- Mounting Options = Panel Mount

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Termination Type = Screw Terminal <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Input Voltage (VAC) = 110, 120 • Contact Rating = 10A @ 240 VAC <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = 7000 Electropneumatic Timing - Industrial <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Mounting Options = Panel Mount • Mode of Operation = Off-Delay • Delay Time = 1.5 seconds to 15 seconds • Type of Control = Knob • Repeatability, Max. = ± 5% • Approved Standards = CE Approved, CSA Certified, FM Approved, UL Listed • Option = Auxiliary Switch - Two-Step Timing • Approx. Dimensions (L x W x H) (mm [in]) = 114.80 x 65.30 x 71.90 [4.523 x 2.572 x 2.832] 	<p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Contact Arrangement = 2 Form C, DPDT, 2 C/O • Multiple Timing Ranges = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not relevant for lead free process <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Range (?C) = -30 - +75 <p>Other:</p> <ul style="list-style-type: none"> • Brand = Agastat

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)