

Spade and Ring Series Pre-Insulated

.300 Square Spade
.031 Electro-Tinned Copper
16-14 AWG (Blue)

S P A D E & R I N G

| STYLE AND DIMENSIONS | STUD | MAX. INSULATION DIAMETER | | | SEAM | UL | CSA | QUANTITY PER REEL | PART NUMBER | |
|----------------------|------|--------------------------|------|------|------|----|-----|-------------------|-------------|----------|
| | | .147 | .200 | .250 | | | | | | |
| | 4 | X | | | B | / | / | 4000 | 50265 | |
| | | | | X | | B | / | / | 3000 | 50265-8 |
| | | | | | X | | B | / | * | 3000 |
| | | 6 | X | | | W | / | / | 4000 | 50266 |
| | | | | X | | W | / | / | 3000 | 50266-8 |
| | | | | | X | | W | / | * | 3000 |
| | | 8 | X | | | B | / | / | 4000 | 50277 |
| | | | | X | | B | / | / | 3000 | 50277-8 |
| | | | | | X | | B | / | * | 3000 |
| | | 10 | X | | | W | / | / | 4000 | 50278 |
| | | | | X | | W | / | / | 3000 | 50278-8 |
| | | | | | X | | W | / | * | 3000 |
| | 10 | X | | | B | / | / | 4000 | 50289 | |
| | | | X | | B | / | / | 3000 | 50289-8 | |
| | | | | X | | B | / | * | 3000 | 50289-8A |
| | 10 | X | | | W | / | / | 4000 | 50290 | |
| | | | X | | W | / | / | 3000 | 50290-8 | |
| | | | | X | | W | / | * | 3000 | 50290-8A |
| | 10 | X | | | B | / | / | 4000 | 50301 | |
| | | | X | | B | / | / | 3000 | 50301-8 | |
| | | | | X | | B | / | * | 3000 | 50301-8A |
| | 10 | X | | | W | / | / | 4000 | 50302 | |
| | | | X | | W | / | / | 3000 | 50302-8 | |
| | | | | X | | W | / | * | 3000 | 50302-8A |

Recommended Strip Length $\frac{3}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.