

# Products

- O By Type
  - Connectors
  - Electromechanical Components
  - Electronic Modules
  - Fiber Optics
  - Filters
  - Identification & Labeling
  - Passive Components
  - Power Sources
  - RF & Microwave Products
  - **Tooling Products**
  - Touch Screen Displays
  - Tubing, Molded and Harnessing Products
  - Wire, Cable and Cable Assemblies
  - List all product types...
- O By Industry
  - Aerospace & Defense Products
  - Appliance
    Automotive
  - Comm unications
  - Computer & Consumer Electronics
  - Industrial & Comm ercial
  - Instrumentation & Medical
- O By Brand
- O A to Z
  O Product News

## Documentation

- O Find Documents & Drawings
- Find CAD Models
- SPICE/Electrical Models
- NAFTA Certificate of Origin O White Papers

# • Resources

- RoHS Compliance & Alternates
- Cross Reference Products
- Compare Multiple Products
  Check Distributor Inventory
- O Find Authorized Distributors

# • My Account

- O Sign In
- O Register

# • Customer Support

- O Support
  O RoHS Support Center
  O Glossary of Terms
  O eBulletin Newsletter

# 1520237-1 Product Details



#### No Image Available

1520237-1 

#### Power Toggle Switches

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Double Pole Single Throw Configuration (Pole-Throw)
   Toggle Length = 17.30 m m
- Toggle Length = 17.30 m m Toggle Style = Baton
- Bushing Length = 8.74 mm
- Term ination Type = Screw-In Terminal

View all Features | Find Similar Products

### Documentation & Additional Information

#### Product Drawings:

• <u>DIM'S FOR DBL. POLE TOOL HANDLE SW. FOR EUROPEAN USE</u> (PDF, English)

#### Catalog Pages/Data Sheets:

#### **Product Specifications:**

None Available

#### Application Specifications:

• None Available

#### Instruction Sheets:

None Available

#### CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version E)
- <u>3D Model</u> (IGES, Version E)
- 3D Model (STEP, Version E)

### Related Products:

• Tooling

Previous 1 ... [16] 17 18 19 20 Next

Check Pricing & Availability Search for Tooling

Contact Us About This Product

 Product Feature Selector Compare Products

Quick Links

#### List all Docum ents

Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Configuration (Pole-Throw) = Double Pole Single Throw
- Term ination Type = Screw-In Terminal

### **Electrical Characteristics:**

- UL/CSA 125V Current Rating (Amps.) = 16
- UL/CSA 250V Current Rating (Amps.) = 8
- UL/CSA 125V Horse Power Rating (hp) = 1.00

#### Housing Related Features:

- Toggle Length (m m [in]) = 17.30 [0.681]
- Toggle Sty le = Baton

#### Configuration Related Features:

• Bushing Length (mm [in]) = 8.74 [0.344]

#### Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not reviewed for lead free solder process
- RoHS/ELV Compliance History = Always was RoHS compliant

Brand = Alcoswitch

Provide Website Feedback | Contact Customer Support Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support 2008 Tyco Electronics Corporation All Rights Reserved