


# AZ956

## MICROMINIATURE POLARIZED RELAY

### FEATURES

- Microminiature size: up to 50% less board area than previous generation telecom relays
- Meets FCC Part 68.302 1500 V lightning surge
- Low power consumption: 36 mW pickup
- Stable contact resistance for low level signal switching
- Epoxy sealed for automatic wave soldering and cleaning
- UL, CUR file E43203
- All plastics meet UL94 V-0, 30 min. oxygen index



### CONTACTS

<b>Arrangement</b>	SPDT (1 Form C) Bifurcated crossbar contacts
<b>Ratings</b>	Resistive load: Max. switched power: 30 W or 60 VA Max. switched current: 1.0 A Max. switched voltage: 150 VDC or 125 VAC
<b>Rated Load UL</b>	0.5 A at 120 VAC 1.0 A at 30 VDC
<b>Material</b>	Palladium nickel with gold-rhodium overlay
<b>Resistance</b>	< 50 milliohms initially (6 V, 10 mA method)

### COIL (Polarized)

<b>Power At Pickup Voltage (typical)</b>	36 mW
<b>Max. Continuous Dissipation</b>	0.5 W at 20°C (68°F)
<b>Temperature Rise</b>	At nominal coil voltage 8°C (15°F)
<b>Temperature</b>	Max. 105°C (221°F)

### NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Relay has fixed coil polarity.
4. Specifications subject to change without notice.

### GENERAL DATA

<b>Life Expectancy Mechanical Electrical</b>	Minimum operations 1 x 10 <sup>9</sup> 2.5 x 10 <sup>5</sup> at 0.4 A, 125 VAC, resistive 3 x 10 <sup>6</sup> at 1.0 A, 24 VDC, resistive
<b>Operate Time (typical)</b>	1 ms at nominal coil voltage
<b>Release Time (typical)</b>	0.4 ms at nominal coil voltage (with no coil suppression)
<b>Bounce (typical)</b>	At 10 mA contact current 1 ms at operate or release
<b>Dielectric Strength (at sea level)</b>	1500 Vrms contact to coil 500 Vrms between open contacts
<b>Dropout</b>	Greater than 10% of nominal coil voltage
<b>Insulation Resistance</b>	10 <sup>9</sup> ohms min. at 25°C, 500 VDC, 50% RH
<b>Ambient Temperature Operating Storage</b>	At nominal coil voltage -40°C (-40°F) to 70°C (158°F) -40°C (-40°F) to 105°C (221°F)
<b>Vibration</b>	Operational, 40 g, 10–200 Hz
<b>Shock</b>	Operational, 50 g min., 11 ms Non-destructive, 150 g min., 11 ms
<b>Max. Solder Temp. Temp./Time</b>	Vapor phase: 215°C, 40 Sec. Infrared: 215°C, 40 Sec. Double wave: 260°C, 10 Sec.
<b>Max. Solvent Temp.</b>	80°C (176°F)
<b>Max. Immersion Time</b>	30 seconds
<b>Weight</b>	1.8 grams
<b>Enclosure</b>	P.B.T. polyester
<b>Terminals</b>	Tinned copper alloy, P.C.



**AMERICAN ZETTLER, INC.**

[www.azettler.com](http://www.azettler.com)

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM


7/24/02W

# AZ956

## RELAY ORDERING DATA

STANDARD RELAYS						Order Number	
Nominal Coil VDC	Max. Continuous VDC		Coil Resistance $\pm 10\%$		Must Operate VDC	THT Through Hole	SMT
	THT	SMT	THT	SMT			
1.5	4.5	4.0	36	28	1.13	AZ956-1.5DE	AZ956S-1.5DE
3	8.8	8.0	137	113	2.25	AZ956-3DE	AZ956S-3DE
5	14.5	13.3	370	313	3.75	AZ956-5DE	AZ956S-5DE
9	25.5	23.9	1165	1013	6.75	AZ956-9DE	AZ956S-9DE
12	35	35	2250	1800	9.00	AZ956-12DE	AZ956S-12DE
15	42	42	3100	2813	11.30	AZ956-15DE	AZ956S-15DE
24	50	50	4500	4500	18.00	AZ956-24DE	AZ956S-24DE

## MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance:  $\pm .010$ "



**AMERICAN ZETTLER, INC.**

[www.azettler.com](http://www.azettler.com)

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

7/24/02W