



Patch Cords and Test Leads

Pomona®




Patch Cords and Test Leads

All dimensions in inches unless otherwise noted.

Contact your local distributor for price and availability on products made to your specifications.

ULTRA-THIN MICROGRABBER® TEST CLIPS



Designed especially for today's fine pitched SMD's. Clips have a narrow body (.120" wide), and a small flexible shaft (.050" dia. x .910" long). Contact pincers open to .024".

ULTRA-THIN MICROGRABBER® TEST CLIP PATCH CORD

22 AWG Wire, .064 O.D.

RATING: 36 VAC/60 VDC, 1 Amp, ≤15mΩ, +80°C (+176°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
6091-10-*	10"	14.15
6091-20-*	20"	14.15
6091-30-*	30"	14.15

ULTRA-THIN MICROGRABBER® TEST CLIP ONE END ONLY

RATING: 45 VAC, 2 Amps, ≤15mΩ, +80°C (+176°F) Max.

*STD COLORS: Available in 10 colors.

**Pomona
ACCESS**

Part No.	Length	PRICE
6090-40-*	40"	7.20

MINIGRABBER® TEST CLIP TO MINIGATOR TEST CLIP



Hook attaches to component leads up to .060 O.D.

Jaws open to .187.

20 AWG Wire, .087 O.D.


RATING: 45V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
4652-12-*	12"	5.40
4652-24-*	24"	5.40
4652-36-*	36"	5.40
4652-48-*	48"	5.65

MINIGATOR TEST CLIP PATCH CORD



Jaws open to .187.

18 AWG Wire, .144 O.D.

RATING: 45V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
MG-B-4-*	4"	4.20
MG-B-8-*	8"	4.20
MG-B-12-*	12"	4.20
MG-B-24-*	24"	4.20
MG-B-36-*	36"	4.20
MG-B-48-*	48"	4.65
MG-B-60-*	60"	4.65

20 AWG Wire, .087 O.D.


RATING: 45V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
1236-8-*	8"	3.95
1236-12-*	12"	3.95
1236-24-*	24"	3.95
1236-36-*	36"	3.95
1236-48-*	48"	4.40
1236-60-*	60"	4.40

ALLIGATOR TEST CLIP PATCH CORD



Jaws open to .300.

18 AWG Wire, .144 O.D.

RATING: 150V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: Available in 10 colors.

**Pomona
ACCESS**

Part No.	Length	PRICE
90533 AL-B-4-*	4"	4.10
AL-B-8-*	8"	4.10
AL-B-12-*	12"	4.10
AL-B-18-*	18"	4.10
AL-B-24-*	24"	4.10
AL-B-36-*	36"	4.10
AL-B-48-*	48"	4.55
AL-B-60-*	60"	4.55


ALLIGATOR TEST CLIP PATCH CORD KIT

Kit contains 10 patch cords, one ea. of 10 colors.

**Pomona
ACCESS**

Part No.	Length	PRICE
90533 6356-12	12"	39.00
6356-24	24"	39.00
6356-36	36"	39.00
6356-48	48"	43.25
6356-60	60"	43.25

MULTI-STACKING BANANA PLUG TO ALLIGATOR TEST CLIP



Jaws open to .300.

18 AWG Wire, .144 O.D.

RATING: 150V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: Available in 10 colors.

**Pomona
ACCESS**

Part No.	Length	PRICE
90258 1166-8-*	8"	4.10
1166-12-*	12"	4.10
1166-24-*	24"	4.10
1166-36-*	36"	4.10
1166-48-*	48"	4.45
1166-60-*	60"	4.45

**Pomona
ACCESS**

Part No.	Length	PRICE
90258 6357-12	12"	39.00
6357-24	24"	39.00
6357-36	36"	39.00
6357-48	48"	42.25
6357-60	60"	42.25

BANANA PLUG TO ALLIGATOR CLIP PATCH CORD KIT

Kit contains 10 patch cords, one ea. of 10 colors

MULTI-STACKING BANANA PLUG TO MINIGATOR TEST CLIP



Jaws open to .187.

20 AWG Wire, .087 O.D.


RATING: 45V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
90571 3220-8-*	8"	3.95
3220-12-*	12"	3.95
3220-24-*	24"	3.95
3220-36-*	36"	3.95
3220-48-*	48"	4.40
3220-60-*	60"	4.40

MICROGATOR TEST CLIP PATCH CORD



Jaws open to .220.

20 AWG Wire, .087 O.D.

RATING: 45V, 5 Amps, +50°C (+122°F) Max.

*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
90548 1613-4-*	4"	4.85
1613-8-*	8"	4.85
1613-12-*	12"	4.85
1613-24-*	24"	4.85
1613-36-*	36"	4.85
1613-48-*	48"	4.85

Alligator clip features a smooth jaw, and has a narrow (.063) width nose.

*COLOR CODE: -0 Black, -1 Brown, -2 Red, -3 Orange, -4 Yellow, -5 Green, -6 Blue, -7 Violet, -8 Gray, -9 White

Pomona Electronics

Sales: (909) 469-2900 FAX: (909) 629-3317 Tech. Support: (800) 241-2060
© 2001 Pomona Electronics. Specifications and prices subject to change without notice. Printed in U.S.A.

www.pomonaelectronics.com