



A	09664547513	3	6	4.20	3.5							 All Dim. in mm Orig. Size DIN A 3	D-Sub 37 poles straight female connector with press-in termination, version contact grounding pins and screw lock.	Maßstab/ Scale 2,5:1
	09664546513	2	6	4.20	3.5				Detail.	14/02/00	jfb			
	09664545513	0.76 μ m Au	6	4.20	3.5				Insp.					
	09664547517	3	5.7	4.35	3.9				Stand.				TB 0966454x51x	Blatt/ Page 3
	09664546517	2	5.7	4.35	3.9	27980	05/03/01	jfb	HARTING EURL F-95972 Paris					
	09664545517	0.76 μ m Au	5.7	4.35	3.9	26574	14/02/00	jfb						
	Part number	Performance level	A \pm 0.2	B \pm 0.2	max.C	Mod.	Dat.	Name				Sub.		

09 66 454 6513**D-Sub - S PCB connector**

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 6.0 mm
Board fixing	with grounding press-in board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 2
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)

09 66 454 5517**D-Sub - S PCB connector**

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 5.7 mm
Board fixing	with grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level S4
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

09 66 454 5513

D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 6.0 mm
Board fixing	with grounding board locks
flange	with screw lock UNC 4-40
Performance level	Performance level S4
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

09 66 454 6517**D-Sub - S PCB connector**

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 5.7 mm
Board fixing	with grounding press-in board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 2
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

09 66 454 7517**D-Sub - S PCB connector**

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 5.7 mm
Board fixing	with grounding press-in board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 3
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

09 66 454 7513**D-Sub - S PCB connector**

Other applications

gender	female connector, straight
Termination	Press-In termination
shell	tinned metal shell
Number of contacts	37 way
Flange heigh	flange height 6.0 mm
Board fixing	with grounding press-in board locks
flange	with screw lock UNC 4-40
Performance level	Performance level 3
Material	LCP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)