


PIN OUT

| P1 | WIRE COLOR | P2 |
|----|--------------|----|
| 1 | ORANGE/WHITE | 1 |
| 2 | ORANGE | 2 |
| 3 | GREEN/WHITE | 3 |
| 6 | GREEN | 6 |
| 4 | BLUE | 4 |
| 5 | BLUE/WHITE | 5 |
| 7 | BROWN/WHITE | 7 |
| 8 | BROWN | 8 |



Material:

- Conductor: 26AWG 7*0.16±0.015mm
- Conductor Insulation color coding: (1)White/Orange, (1)Orange, (1)White/Green, (1)Green, (1)Blue, (1)White/Blue, (1)White/Brown, (1)Brown
- Included printing on cable jacket: *CM (UL) C(UL) 4P 26AWG UTP CAT.6 PATCH CABLE ISO/IEC & EN & ANSI/TIA-568-C.2*
- Cable Assembly: White cable tie, Wiring T568B color, Plug RJ45 8P8C 3μ pc UL 94V-2
- Cable Jacket color: Red, Yellow, Green or Blue
- Length: L±3%
 • Dielectric strength: 2.5KV dc-2seconds
 • Working temperatures: -20°C~60°C

Order Code: A-MCU60xxx/x-R
 Order lengths in meter: 0.5, 1, 2, 3, 5, 7, 10, 15, 20, 30
 Order color: Red, Yellow, Green, Blue

Unit: mm



| Scale | | | | | | Date | Name | Title |
|-----------|-----|-----|--------------|----------|--------|--------------------------------------------------------------------------------------------------------|--------|----------------------------------------|
| TOLERANCE | | | | | | Drawn | Wilson | Cat6 UTP Patch cable 26AWG, colored |
| X. | ±X | | | | | Approved | Groll | ASSMANN WSW-No. |
| X.X | ±X | | | | | | | A-MCU60xxx/x-R |
| X.XX | ±X | | | | | | | Drawing-No. |
| DIM | TOL | | | | | | | rev01 |
| X.° | ±X° | ① | Update | 20.02.13 | Wilson | | | Replace |
| X.X° | ±X° | | Modification | Date | Name | 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us | | 1/1 |
| Angle | TOL | Id. | | | | | | |