





Solutions

Products and Services

Support

Your Business

Company

You are here: Home > Products > Power Distribution > Transfer Switches > Rack-mount Transfer Switches

Rack-mount Transfer Switches

Rack ATS, 100-120V, 15A, 5-15P In, (10) 5-15R Out



APC Rack-mount Transfer Switches, Input: 100V, 120V, Input Connections: NEMA 5-15P, Cord Length: 8 feet (2.44 meters), Output: 100V, 120V, Output Connections: NEMA 5-15R

Includes: Rack Mounting brackets, User Manual

Standard Lead Time: Usually in Stock

AP7750A

Email Technical Specifications

Printer Friendly

Product Category

Rack Power Distribution (6)

Row Power Distribution (6)

Room Power Distribution (1)

Transfer Switches

> Wall-mount Transfer Switches



> **Rack-mount Transfer Switches**



[More Images](#)

[Return to Power Distribution](#)

[Technical Specifications](#) | [Product Overview](#) | [Documentation](#) | [Software & Firmware](#) | [Options](#)

Output	
Nominal Output Voltage	100V, 120V
Maximum Total Current Draw per Phase	15A
Output Connections	(10) NEMA 5-15R 
Input	
Nominal Input Voltage	100V, 120V
Input Frequency	50/60 Hz
Regulatory Derated Input Current (North America)	12A
Input Connections	NEMA 5-15P 
Cord Length	8 feet (2.44 meters)
Number of Power Cords	2
Acceptable Input Voltage	100-125 VAC
Maximum Input Current per phase	15A
Load Capacity	1440 VA
Physical	
Net Weight	10.35 lbs. (4.70 kg)
Maximum Height	1.72 inches (44 mm)
Maximum Width	17.00 inches (432 mm)
Maximum Depth	9.30 inches (236 mm)
Shipping Weight	14.25 lbs. (6.48 kg)
Shipping Height	4.50 inches (114 mm)
Shipping Width	23.63 inches (600 mm)
Shipping Depth	14.00 inches (356 mm)
Color	Black
Environmental	
Operating Environment	23 - 113 °F (-5 - 45 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-13 - 149 °F (-25 - 65 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)
Conformance	

Regulatory Approvals	FCC Part 15 Class A, ICES-003, TUV-C, TUV-NURTL, VCCI Class A
Standard Warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOL	Available in Documentation tab
Battery Directive	Compliant
Battery Notes	Contains Lithium Battery

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[AP7750A](#)