


DK 4 Q*



DK 4 QV*



Approvals	
Dimensions (W x L x H with TS 35) in mm	
Rated data	
Rated voltage	V
Rated current	A
Rated cross-connection	mm ² /AWG
Rated impulse voltage	kV
Pollution severity	
Ordering data	
Version	Type
PA	DK 4 Q
blue PA	DK 4 Q

6 x 54 x 60.5			
IEC 60 947-7-1	UL	CSA	
500	300	300	
32	27	10	
4	22...12	26...12	
6			
3			
Type	Part No.	Qty.	
DK 4 Q	0590160000 ¹⁾	100	
DK 4 Q	0590180000 ¹⁾	100	

6 x 54 x 60.5			
IEC 60 947-7-1	UL	CSA	
500	300	300	
32	27	10	
4	22...12	26...12	
6			
3			
Type	Part No.	Qty.	
DK 4 QV	0363660000 ^{*1)}	100	
DK 4 QV	0363680000 ^{*1)}	100	

End plate	
Version	Type
PA	AP (1.5)
blue PA	AP (1.5)
Partition	
Version	Type
PA	WTW (Ex)
blue PA	WTW (Ex)
HP	TSch 6
Small partition	TSch 6

Cross-connection	
2-pole	Q 2
3-pole	Q 3
4-pole	Q 4
10-pole	Q 10
2-pole	QB 2
3-pole	QB 3
4-pole	QB 4

Clampable conductors	
solid H07V-U	mm ²
stranded H07V-R	mm ²
flexible H07V-K	mm ²
flexible H07V-K und AEH DIN 46 228/1	
with / without Plastic insul. collar	mm ²
Gauge pin acc. to 60 947-1	Size
Cont. current of terminal for conductor size	
Cont. current of Cross-connection WQV/ZQV 2...5-pole	A
Cont. current of Cross-connection WQV/ZQV 6...10-pole	A

Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver Type DMS 2	
Insulation stripping length/clamping screw/screwdriver blade	

Accessories	
Cover	
Screw für Cover	
Cross-section link	VL 2
Connection sleeve	VH
Fixing screw	BS
Marking tags DEK	DEK 6

Type	Part No.	Qty.
AP (1.5)	1397160000	20
AP (1.5)	1397180000	20
WTW (Ex)	1058800000	20
TSch 6	0190260000	100

2-pole	Q 2	0336400000	50
3-pole	Q 3	0336500000	50
4-pole	Q 4	0336600000	50
10-pole	Q 10	0368600000	20
2-pole	QB 2	0482700000 ²⁾	100
3-pole	QB 3	0482800000 ²⁾	50
4-pole	QB 4	0482900000 ²⁾	50

mm ²	0.5...6
mm ²	0.5...4
mm ²	0.5...4
mm ²	0.5...4
Size	A 3
	41 A/6 mm ²
A	32
A	32

Nm	0.5...1.0
	2
	9/M 3/3.5 x 0.6

Type	Part No.	Qty.
AD 4	0303400000	50
BSK M 2.5 x 18	0303300000	100
VL 2	0446700000	50
VH	1056500000	100
BS	0343100000	100
DEK 6		

Type	Part No.	Qty.
AP (1.5)	1397160000	20
AP (1.5)	1397180000	20
WTW (Ex)	1058800000	20
TSch 6	0190260000	100

2-pole	Q 2	0336400000	50
3-pole	Q 3	0336500000	50
4-pole	Q 4	0336600000	50
10-pole	Q 10	0368600000	20
2-pole	QB 2	0482700000 ²⁾	100
3-pole	QB 3	0482800000 ²⁾	50
4-pole	QB 4	0482900000 ²⁾	50

mm ²	0.5...6
mm ²	0.5...4
mm ²	0.5...4
mm ²	0.5...4
Size	A 3
	41 A/6 mm ²
A	32
A	32

Nm	0.5...1.0
	2
	9 / M 3/3.5 x 0.6

Type	Part No.	Qty.
AD 4	0303400000	50
BSK M 2.5 x 18	0303300000	100
VL 2	0446700000	50
VH	1056500000	100
BS	0343100000	100
DEK 6		

¹⁾ Finger-safe cross-connection with ADP 4 cover profiles (see main catalogue)

²⁾ Max. 2.5 mm² when using QB cross-connection comb

* With mounting option for shield bus LS 2.8 Part No. **1056400000**