

AMI200-9

Slim Type for IBASE MI910 Mini-ITX Motherboard

AMI200-8

Slim Type for IBASE MB899 Mini-ITX Motherboard

Fanless System



Features

- Mini-ITX system with IBASE MI910E Mini-ITX motherboard
- Chassis with Intel® Core™2 Duo T7500 processor, 2.2GHz
- Available in silver color
- One 2.5" HDD drive bay
- Fanless operation
- Wall mount kit included

Specifications

System Mainboard	MI910E
Construction	Aluminum
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	Audio, 1x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS
Storage	1x 2.5" 160GB HDD
Power Supply	80W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	199mm(W) x 232mm(D) x 63.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

AMI200-9	Aluminum System with MI910E, Intel® T7500 (2.2GHz) CPU, 2GB DDR2, 2.5" 320GB HDD, ID392 DVI board, 110W DC-DC converter, 80W power adaptor
----------	--

Fanless System



Features

- Mini-ITX system with IBASE MB899HF Mini-ITX motherboard
- Chassis with Intel® Celeron® 440 processor, 1.83GHz
- Available in silver color
- One 2.5" HDD drive bay
- Fanless operation
- Wall mount kit included

Specifications

System Mainboard	MB899HF
Construction	Aluminum
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	Audio, 2x LAN, 4x USB, COM, VGA, TV out, SPDIF, 1394, KB/MS
Storage	1x 2.5" 160GB HDD
Power Supply	80W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	199mm(W) x 232mm(D) x 63.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

AMI200-8	Aluminum System with MB899HF, Intel® 440 (1.83GHz) CPU, 1GB DDR2, 2.5" 320GB HDD, 110W DC-DC converter, 80W power adaptor
----------	---



01
Motherboards

02
Disk-Size SBCs

03
CPU Modules

04
PC 104 Plus

05
CPU Cards

06
RISC SBCs

07
Embedded Systems