



Recommended PCB Layout  
(Bottom View)

**Materials and Finish**

Housing: High Temperature Thermoplastic, 15% Glass Filled Pink (Pantone 701C) Color UL 94V-0 Rated

**Terminals:**

Pin 1: Brass, Matte Tin Plated  
Pin 2, 5: Phosphor Bronze Matte Tin Plated

**Electrical Characteristics**

Contact Resistance:  
Before Test: 50 milliohms Max.  
After Durability Test:  
100 milliohms Max.

Insulation Resistance:  
More than 100 Megohms at 500V DC

Dielectric Strength:  
500V AC RMS for 1 minute

Operating Temp:  
-25°C to +85°C

**Mechanical Characteristics**

Insertion Force:  
0.4kg - 3.0kg

Extraction Force:  
0.3kg - 3.0kg

Durability: 5000 mating cycles



Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	9/22/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	07/14/05
A1	6/2/06	Release Drawing	H. MA	N/A		
B1	08/12/09	ECO #09-039	S. Vien	H. MA		
B2	11/10/10	ECO #10-078	S. Vien	H. MA	UNITS	mm
B3	05/25/11	ECO #11-036	S. Vien	H. MA		

**STX-3120-3B-701C**

Stereo Jack, 3 Position, RoHS Compliant

Meets PC99 spec, Pink Color



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Kycon:](#)

[STX-3120-3B-701C](#)