


Spade and Ring Series Uninsulated


.300 Notched Spade Insulation Piercing — 2 Barbs

C
N
I
R
&
E
D
A
P
S

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	4	.050-.070	— —	5000	—	.020	Brass	3E1-4-2
		Pre Tinned Brass	3E2-4-2					
		.075-.125	— —	5000	—	.020	Brass	3E1-4
			Pre Tinned Brass	3E2-4				
	6	.050-.070	— —	5000	—	.020	Brass	3E1-6-2
			Pre Tinned Brass	3E2-6-2				
		.075-.125	— —	5000	—	.020	Brass	3E1-6
			Pre Tinned Brass	3E2-6				
	8	.050-.070	— —	5000	—	.020	Brass	3E1-8-2
			Pre Tinned Brass	3E2-8-2				
		.075-.125	— —	5000	—	.020	Brass	3E1-8
			Pre Tinned Brass	3E2-8				

Spade and Ring Series Uninsulated

.175 Ring 22-16 AWG

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	0	None	✓ ✓	7000	$5/32 \pm 1/32$.020	Brass	40001
							Pre Tinned Brass	40002
	.083	None	— —	7000	$5/32 \pm 1/32$.020	Brass	40022
							Brass	40005
	2	None	✓ ✓	7000	$5/32 \pm 1/32$.020	Pre Tinned Brass	40006
							Cadmium Plated Brass	40007
	.115	None	✓ ✓	7000	$5/32 \pm 1/32$.020	Brass	40021
							Brass	40017
	3	None	✓ ✓	7000	$5/32 \pm 1/32$.020	Pre Tinned Brass	40018
							Brass	3800M87
	.130	None	— —	7000	$5/32 \pm 1/32$.020	Brass	3800M87