

181-44013



Article Number: 181-44013

Solid Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, White, 30ft/Box



Base Data

Local Order Number 181-44013

Type SD4X4

Color White (WH)

- Features and Benefits**
- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
 - Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
 - Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

Short Description Solid Wall Wiring Duct, 4" X 4", Non-Adhesive, PVC, White, 30ft/Box

Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 4.0 "

Width W (metric) 101.6 mm

Width W2 (imperial) 4.0 "

Width W2 (metric) 101.6 mm

Width W6 (imperial) 1.5 "

Width W6 (metric) 38.1 mm

Height H (imperial) 4.06 "

Height H (metric) 103.1 mm

Mounting Hole Centers (imperial) 4.0 "

Mounting Hole Centers (metric) 101.6 mm

Logistics and Packaging

Quantity per box

Package Quantity (imperial) 30

Package Quantity 9.1

Carton Quantity 120

Material and Specifications

Material Polyvinylchloride (PVC)

| | |
|--------------------------------------|--------------------|
| Material Shortcut | PVC |
| CSA Certified | Yes |
| Flammability | self-extinguishing |
| Operating Temperature | +122 °F (+50 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | CSA UL |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | Yes |
| UL Recognized (US) | Yes |