


VICOR CONFIDENTIAL

THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED, USED, OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT PERMISSION OF VICOR CORP.

REV	DESCRIPTION	DATE	APPROVED
A	RELEASED PER ECO #1607 D.Z.	6/9/89	P.M.
A1	REVISED PER E910164 JFW	6/10/91	BJR.
B	REVISED PER E930005 JFW	1/19/93	WWP.
C	REVISED PER E931325 JC	2/23/94	JJG
D	REVISED PER E940748 RCM	10/14/94	DPK
E	REVISED PER E970236 DPK	6/19/97	RCM

TO-220
(SEE NOTE 2)



MARKING: VENDOR OR VICOR #02838
VENDOR DATE CODE
VENDOR I.D.
POLARITY

ELECTRICAL CHARACTERISTICS @ T_J=25°C (UNLESS OTHERWISE SPECIFIED)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST CONDITIONS
D.C. REVERSE LEAKAGE	I _R			20	mA	V _R =35V
D.C. REVERSE LEAKAGE	I _R			250	mA	V _R = 35V, T = 125°C
INSTANTANEOUS FORWARD VOLTAGE DROP	V _F			.50	V	SEE FIGURE #1 I _F = 10.0A
INSTANTANEOUS FORWARD VOLTAGE DROP	V _F			.60	V	SEE FIGURE #1 I _F = 20.0A
THERMAL RESISTANCE JUNCTION TO CASE	R _{o(jc)}			3	°C/W	
OPERATING TEMPERATURE	T _J	-40 TO +150			°C	
AVALANCHE BREAKDOWN VOLTAGE	A _v	35			V	SEE FIGURE #1 (T _J) TEST TEMP =25°C
AVALANCHE BREAKDOWN ENERGY	E _{as}	15			mJ	PER FIGURE #1




FIG. #1

NOTES

- LEADS TO BE SOLDER TINNED TO WITHIN .08 OR LESS OF BODY.
- MECHANICAL SPECIFICATIONS FOR TO-220 OUTLINE PER VICOR 16435.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ±1/64 .XX ± .01 ± 1° XXX ± .001	APPROVALS	DATE	VICOR
	DRAWN:	10/88	
THIRD ANGLE PROJECTION	CHECKED:		TO-220 DUAL SCHOTTKY 35V RECTIFIER
DO NOT SCALE DRAWING	SIZE	FSCM NO.	DWG. NO.
	C	67131	02838
	SCALE	NONE	REV. E
			SHEET 1 OF 1