

HOOK-UP WIRE

- ◆ Automotive Wire
- ◆ Teflon® Wire
- ◆ 300V Solid Wire
- ◆ 300V Stranded Wire
- ◆ 600V Stranded Wire
- ◆ Speaker Wire
- ◆ Black/Red Bonded Speaker Wire



Features:

- ***Broad Line – 500 Types***
- ***Packaged in a variety of lengths, gauges and colors***
- ***Shrink wrapped spools***
- ***Small quantity packages available***



ELECTRONICS, INC.

HOOK-UP WIRE

PRODUCT/APPLICATION INFORMATION

AUTOMOTIVE WIRE (WA SERIES) – 80° C

- GAUGES:** 18-16-14-12-10
VOLTAGE RATING: 120 Volts
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
PACKAGES: 10, 15, 20, 30 & 40 Feet
SPOOLS: 100 Feet
STRAND COUNT: 18ga = 16 strand
 All others = 19 strand
- APPLICATIONS:**
- Used in all automotive and truck applications
 - J1128 industry certification

TEFLON® WIRE (WT SERIES) – 200° C

- GAUGES:** 26-24-22-20-18
VOLTAGE RATING: 600 Volts
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
- SPOOLS:** 25 and 100 feet
- Silver plated copper conductor
 - Teflon® (TFE) insulation
 - Resistance to oils, alkalies, acids, flame and moisture
 - Meets Mil 16878/4 and Mil 22759/11 specs
- STRAND COUNT:** 22, 20, 18ga = 19 strand
 24, 26ga = 7 strand
- APPLICATIONS:**
- All hi-temp or hi-rel applications
 - Used in critical, high performance; military; commercial; racing

300V SOLID WIRE (WHS SERIES) – 90° C

- GAUGES:** 26-24-22-20-18
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
- SPOOLS:** 25 and 100 feet
- UL Style 1007
 - CSA TR-64/1569
 - Passes UL VW-1.S vertical flame test
 - OSHA acceptable
- APPLICATIONS:**
- Internal wiring of electrical and electronic equipment
 - Internal wiring of panels, meters, computers, business machines, appliances & control panels
 - Point to point wiring where 300V required



300V STRANDED WIRE (WH SERIES) – 90° C

- GAUGES:** 26-24-22-20-18-16
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
- SPOOLS:** 25 and 100 feet
- UL Style 1007
 - CSA TR-64/1569
 - Passes UL VW-1.S vertical flame test
 - OSHA acceptable
 - All tinned copper
- STRAND COUNT:** 22, 24, 26ga = 7 strand
 20ga = 10 strand
 18ga = 16 strand
 16ga = 26 strand
- APPLICATIONS:**
- Internal wiring of electrical and electronic equipment
 - Internal wiring of panels, meters, computers, business machines, appliances & control panels
 - Point to point wiring where 300V required

600V STRANDED WIRE (WH6 SERIES) – 105° C

- GAUGES:** 18-16-14-12-10
COLORS: Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Gray, White
- SPOOLS:** 25 and 100 feet
- UL Style 1015
 - CSA type TEW
 - UL VW-1.S vertical flame test
 - OSHA acceptable
 - All tinned copper
- STRAND COUNT:** 10ga = 105 strand
 12ga = 65 strand
 14ga = 41 strand
 16ga = 26 strand
 18ga = 16 strand
- APPLICATIONS:**
- Internal wiring of electrical, electronic equipment and machinery
 - Internal wiring of panels and meters
 - Point to point wiring where 600V required

SPEAKER WIRE (CLEAR)

- GAUGES:** 22/2-20/2-18/2-16/2-14/2-12/2-10/2
SPOOLS: 25 and 100 feet
- OSHA acceptable
- APPLICATIONS:**
- Lamps, radios, jukeboxes, HiFi & stereo

BLACK/RED BONDED SPEAKER WIRE

- GAUGES:** 18/2-16/2-14/2-12/2-10/2
SPOOLS: 25 and 100 feet
- OSHA acceptable
- APPLICATIONS:**
- Easy identification
 - Stereos, lamps, automotive, truck



NTE Electronics, Inc.
 44 Farrand Street, Bloomfield, NJ 07003
 Phone: 973-748-5089
 Fax: 973-748-6224
 www.nteinc.com