


断面 A-A SECT



断面 B-B SECT

NOTES:

- 1. APPLICABLE HDR HSG: 172520 (2.5 PITCH)
172890 (2.0 PITCH)
- 2. PRODUCT SPEC: 108-5163
- 3. CRIMPING SPEC: 114-5062
COMMON APPLICATOR FOR 2/25mm PITCH
HDR HSG: P/N 755764-□
EXCLUSIVE APPLICATOR FOR 25mm PITCH
HDR HSG: P/N 752829-□
- 4. INSTRUCTION SHEET: IS-206J, 207J, 208J

注:

- 1. 適用ハウジング型番: 172520 (2.5mmピッチ用)
172890 (2.0mmピッチ用)
- 2. 製品規格: 108-5163
- 3. 取付通用規格: 114-5062
2/25mmピッチ用ハウジング適用アクリク型番: 755764-□
25mmピッチ用ハウジング専用アクリク型番: 752829-□
- 4. 取扱説明書: IS-206J, 207J, 208J

1.2	+0.05 DIA. 1.2~1.6	172797-2	PRE-TINNED BRASS 0.2t	172781-2
0.95	+0.1 DIA. 1.2~1.6	172797-1	鍍めつき 黄銅0.2t	172781-1
A REF	APPLICABLE PCB HOLE AND THK	LOOSE PIECE CONTACT P/N	MATERIAL	PART NO.
参考寸法	適用基板穴径と板厚	172797-1用	材料	型番

寸法: 1:1 DIMENSIONS IN MM DO NOT SCALE PRINT

PRINT DIST

CIS BY AMP (Japan) LTD. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND OR PATENTS PENDING		AMP 東京エレクトロニクス株式会社 TOKYO, JAPAN	
WIRE RANGE 0.05-0.15 — AVG 20-26	INSULATION DIA 1.1~1.4	品名 ロ-プロファイルミニオンコンタクト (LOW PROFILE MINI AMP-IN CONTACT)	
MATERIAL 表参照 (SEE TABLE)	PL FINISH	SIZE LOC C J	品番 (NO) C-172781
DR B: 再作成 (REDRAWN)	DE M. Yoshida	SCALE 10-1	REV B
LTR: REVISION RECORD DR: CHK: DATE		SHEET	

CUSTOMER DRAWING 参考図面

- [Home](#)
- [Part Number Search](#)
- [Document Search](#)
- [Text Search](#)
- [Alternate Part Search](#)
- [Multiple Part Comparison](#)
- [Alphabetical Search](#)
- [Brand Search](#)
- [Industry Product Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Competitor Cross Reference](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Current Brand View	View All Tyco Electronics Brands Click to activate links to all other products
AMP	

Printed Circuit Board Terminals and Disconnects

Low Profile Miniature AMP-IN Connectors

AMP **172781-1** **Active** [Active](#)

(Tyco Electronics P/N: 172781-1)

[Search for Parts](#) | Previous **[1]** [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information		
General Information	eCommerce	Related Part Information
<input type="checkbox"/> General Info <input type="checkbox"/> Sales Info <input type="checkbox"/> Assembly Subcontractors	<input type="checkbox"/> Pricing <input type="checkbox"/> Product Availability	

Searchable Features:	
Brand:	AMP
Product Type:	Contact
Wire Range (mm [AWG]):	0.05-0.15 ² [30-26]
Insulation Diameter (mm [in]):	1.10-1.80 [.043-.071]
Hole Diameter (mm [in]):	0.79 [0.031]
Packaging Method:	Strip

Other Properties:	
Housing Color:	Natural
Contact Material:	Brass
Contact Mating Area Plating:	Pre-Tin
PCB Thickness (mm [in]):	1.19 – 1.60 [0.047 – 0.063]
Comment:	Machine applied applicator required.

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)