



Straight To Straight Plug Lead Assemblies

Part Number:- 123680/OF-OF/1.2/Colour
Standard Colours. Red Black
Features. 1.0mm² c.s.a. 3.6mm Ø Nom.o/d
Multistranded very flexible copper core. 7/36/0.071
Double Skin Silicone Insulated. Bi-coloured layers.

IEC 61010 Rating.
Measurement Category. 1000V CAT III/600V CAT IV
Current Rating. 20 Amp
Insulation Category. Double/Reinforced.
Pollution Degree. Two (2)

Silvertronic confirm that the product(s) listed have been designed, manufactured and tested to and are therefore fully compliant to:

IEC61010-031:2002 (First Edition) + Amd. 1:2008.

Together with the corresponding UL and CSA Standards, and are subject of a CB Scheme report. All products marked as per IEC requirements. UL and CSA marking upon request.


All testing carried out by independent third party test house and CB Test Laboratory,

MET Laboratories Inc. Baltimore MD 21230 USA

The product(s) also meet the requirements of the Low Voltage Directive and where applicable comply with HSE GS.38.

119054 CUT 1.2Metre

DOUBLE SKIN SILICONE CABLE



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Silvertronic:

[123680/OFOF/1.2/B](#) [123680/OFOF/1.2/BI](#) [123680/OFOF/1.2/G](#) [123680/OFOF/1.2/R](#) [123680/OFOF/1.2/W](#)
[123680/OFOF/1.2/Y](#) [123680/ORSK/1.2/B](#) [123680/ORSK/1.2/R](#)