




HEYClip™ Snap Rivets

- Designed for **fast and easy installation with no tools** - just fingertip pressure required.
- Simply place rivet into the hole and press down on the head to fasten; legs expand to securely fasten components.
- To release, simply pull up on rivet head section.
- Round head provides a clean, finished look.
- Part Description Key: PR X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Material: Nylon 6. Nylon 6/6 UL 94V-0 available by special order, consult Heyco.
- Standard Pack - 1,000/bag.

WILL FIT THESE PANELS						PART NO.			DESCRIPTION	PART DIMENSIONS						EXTRACTION FORCE		
MOUNTING HOLE DIA.		PANEL THICKNESS				Black	White	V-0 Black *		A Length		B Head Height		C Head Diameter		N	Style	
in.	mm.	Min.	Max.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.			mm.
PR Series																		
.083	2,1	.02	0,6	.05	1,2	9296	9297	9296F	PR 083-024	.10	2,4							
		.05	1,3	.08	2,0	9300	9301	9300F	PR 083-051	.13	3,2							
		.08	2,1	.11	2,8	9302	9303	9302F	PR 083-083	.16	4,0							
		.11	2,9	.14	3,6	9304	9305	9304F	PR 083-114	.19	4,8	.05	1,2	.17	4,2	29	2	
		.15	3,7	.17	4,4	9306	9307	9306F	PR 083-146	.22	5,6							
		.17	4,4	.20	5,0	9308	9309	9308F	PR 083-173	.25	6,4							
		.04	1,0	.08	2,0	9020	9021	9020F	PR 102-039	.13	3,2							
		.08	2,0	.12	3,0	9022	9023	9022F	PR 102-082	.17	4,2							
.102	2,6	.11	2,7	.14	3,6	9024	9025	9024F	PR 102-106	.19	4,8							
		.13	3,4	.17	4,3	9026	9027	9026F	PR 102-134	.22	5,6							
		.17	4,3	.21	5,2	9310	9311	9310F	PR 102-169	.25	6,4							
		.20	5,1	.24	6,0	9312	9313	9312F	PR 102-201	.28	7,2							
		.04	1,0	.08	2,0	9028	9029	9028F	PR 122-039	.14	3,5							
		.08	2,0	.12	3,0	9030	9031	9030F	PR 122-079	.18	4,5							
		.12	3,0	.16	4,0	9032	9033	9032F	PR 122-118	.22	5,6							
		.16	4,0	.19	5,0	9034	9035	9034F	PR 122-157	.26	6,5							
.122	3,1	.20	5,0	.24	6,0	9036	9037	9036F	PR 122-197	.30	7,5							
		.22	5,5	.26	6,5	9038	9039	9038F	PR 122-217	.32	8,0	.06	1,6	.25	6,4	78	2	
		.26	6,5	.30	7,5	9040	9041	9040F	PR 122-256	.35	9,0							
		.30	7,5	.34	8,5	9042	9043	9042F	PR 122-295	.39	10,0							
		.45	11,5	.51	13,0	9314	9315	9314F	PR 122-453	.57	14,5							
		.81	20,5	.85	21,5	9316	9317	9316F	PR 122-807	.91	23,0							
		.05	1,2	.08	2,1	9044	9045	9044F	PR 142-047	.14	3,5							
		.08	2,1	.12	3,0	9046	9047	9046F	PR 142-083	.18	4,5							
.142	3,6	.11	2,7	.14	3,6	9048	9049	9048F	PR 142-106	.20	5,0							
		.12	3,0	.16	4,0	9050	9051	9050F	PR 142-118	.22	5,6	.06	1,6	.25	6,4	118	1	
		.15	3,7	.18	4,6	9052	9053	9052F	PR 142-146	.24	6,0							
		.18	4,5	.22	5,5	9054	9055	9054F	PR 142-177	.28	7,0							
		.22	5,5	.26	6,5	9056	9057	9056F	PR 142-217	.32	8,0							
		.10	2,5	.14	3,5	9058	9059	9058F	PR 161-098	.20	5,0							
		.14	3,5	.18	4,5	9060	9061	9060F	PR 161-138	.24	6,0							
		.18	4,5	.22	5,5	9062	9063	9062F	PR 161-177	.28	7,0							
.161	4,1	.22	5,5	.26	6,5	9064	9065	9064F	PR 161-217	.32	8,0							
		.26	6,5	.30	7,5	9066	9067	9066F	PR 161-256	.35	9,0	.07	1,8	.32	8,0	196	1	
		.30	7,5	.34	8,5	9068	9069	9068F	PR 161-295	.39	10,0							
		.35	9,0	.41	10,5	9318	9319	9318F	PR 161-354	.47	12,0							
		.49	12,5	.55	14,0	9320	9321	9320F	PR 161-492	.61	15,5							

Standard colors black and white.
*Black nylon 6/6 UL 94V-0.



STYLE 1



STYLE 2



Material	Nylon 6
Flammability Rating	94V-2
Temperature Rating (min and max)	-0.4°F (-18°C) to 185°F (85°C)


Quick Specs



HEYClip™ Snap Rivets – Continued

WILL FIT THESE PANELS					PART NO.			DESCRIPTION	PART DIMENSIONS						EXTRACTION FORCE		
MOUNTING HOLE DIA.		PANEL THICKNESS			Black	White	V-0 Black *		A Length		B Head Height		C Head Diameter		N	Style	
in.	mm.	Min.	Max.					in.	mm.	in.	mm.	in.	mm.				
PR Series																	
.201	5,1	.06	1,5	.10	2,5	9070	9071	9070F	PR 201-059	.18	4,5					1	
		.10	2,5	.14	3,5	9072	9073	9072F	PR 201-098	.22	5,6						
		.14	3,5	.18	4,5	9074	9075	9074F	PR 201-138	.26	6,5						
		.18	4,5	.22	5,5	9076	9077	9076F	PR 201-177	.30	7,5	.09	2,2	.35	9,0		245
		.22	5,5	.26	6,5	9078	9079	9078F	PR 201-217	.34	8,5						
		.26	6,5	.30	7,5	9080	9081	9080F	PR 201-256	.37	9,5						
		.30	7,5	.34	8,5	9082	9083	9082F	PR 201-295	.41	10,5						
.232	5,9	.12	3,0	.16	4,0	9322	9323	9322F	PR 232-118	.25	6,3	.11	2,7	.47	12,0	245	
.240	6,1	.10	2,5	.16	4,0	9084	9085	9084F	PR 240-098	.24	6,0	.10	2,5			294	
		.14	3,5	.22	5,5	9324	9325	9324F	PR 240-138	.32	8,0	.12	3,0				

Standard colors black and white.
*Black nylon 6/6 UL 94V-0.



STYLE 1



- Designed for **fast and easy installation with no tools** - just fingertip pressure required.
- Simply place rivet into the hole and press down on the head to fasten; legs expand to securely fasten components.
- To release, simply pull up on rivet head section.
- Round head provides a clean, finished look.
- Part Description Key: PR X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Material: Nylon 6. Nylon 6/6 UL 94V-0 available by special order, consult Heyco.
- Standard Pack - 1,000/bag.
- See Quick Specs on page 2.

HEYClip™ Heat Resistant Snap Rivets

WILL FIT THESE PANELS					PART NO.			DESCRIPTION	PART DIMENSIONS						EXTRACTION FORCE	
MOUNTING HOLE DIA.		PANEL THICKNESS			Tan Nylon 4/6 UL94V-2				A Length		B Head Height		C Head Diameter		N	Style
in.	mm.	Min.	Max.					in.	mm.	in.	mm.	in.	mm.			
PR Tan Series																
.122	3,1	.04	1,0	.08	2,0	9028H		PR 122-039 HR Tan	.14	3,5						2
		.08	2,0	.12	3,0	9030H		PR 122-079 HR Tan	.18	4,5						
		.12	3,0	.16	4,0	9032H		PR 122-118 HR Tan	.22	5,6	.06	1,6	.25	6,4	78	
		.16	4,0	.19	5,0	9034H		PR 122-157 HR Tan	.26	6,5						
		.22	5,5	.26	6,5	9038H		PR 122-217 HR Tan	.32	8,0						
.142	3,6	.05	1,2	.08	2,1	9044H		PR 142-047 HR Tan	.14	3,5					1	
		.08	2,1	.12	3,0	9046H		PR 142-083 HR Tan	.18	4,5	.06	1,6	.25	6,4		118
		.11	2,7	.14	3,6	9048H		PR 142-106 HR Tan	.20	5,0						
		.12	3,0	.16	4,0	9050H		PR 142-118 HR Tan	.22	5,6						
.161	4,1	.10	2,5	.14	3,5	9058H		PR 161-098 HR Tan	.20	5,0					1	
		.14	3,5	.18	4,5	9060H		PR 161-138 HR Tan	.24	6,0						
		.18	4,5	.22	5,5	9062H		PR 161-177 HR Tan	.28	7,0	.07	1,8	.32	8,0		196
		.22	5,5	.26	6,5	9064H		PR 161-217 HR Tan	.32	8,0						
		.30	7,5	.34	8,5	9068H		PR 161-295 HR Tan	.39	10,0						

Standard color tan (beige).

ALL NEW PRODUCTS!



- Molded from Nylon 4/6 94V-2 - **heat resistant to 266°F (130°C)**.
- Automotive **tan** (beige) color.
- Designed for fast and easy installation with no tools - just fingertip pressure required.
- Simply place rivet into the hole and press down on the head to fasten; legs expand to securely fasten components.
- Part Description Key: PR X-Y where X = Mounting Hole Diameter (inches) and Y = minimum Panel Thickness (inches).
- Standard Pack - 1,000/bag.

STANDARD PACK 1,000/BAG

Material Nylon 4/6
Flammability Rating 94V-2
Temperature Rating (min and max) -0.4°F (-18°C) to 266°F (130°C)

Quick Specs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Heyco:

[9058H](#) [9046](#) [9046F](#) [9316](#) [9030F](#) [9314](#) [9052](#) [9057](#) [9325](#) [9028H](#) [9035](#) [9064F](#) [9021](#) [9078F](#) [9311](#) [9030H](#)
[9044F](#) [9309](#) [9302](#) [9028F](#) [9026F](#) [9313](#) [9304F](#) [9073](#) [9322F](#) [9046H](#) [9306](#) [9024](#) [9060](#) [9031](#) [9054F](#) [9078](#) [9063](#)
[9318](#) [9044H](#) [9034H](#) [9050F](#) [9024F](#) [9079](#) [9058](#) [9060F](#) [9321](#) [9060H](#) [9308](#) [9050H](#) [9302F](#) [9048H](#) [9029](#) [9084F](#)
[9062H](#) [9049](#) [9042F](#) [9065](#) [9312F](#) [9070](#) [9297](#) [9082F](#) [9061](#) [9076F](#) [9307](#) [9034F](#) [9304](#) [9315](#) [9028](#) [9056F](#) [9050](#)
[9075](#) [9300F](#) [9052F](#) [9068H](#) [9064](#) [9069](#) [9310F](#) [9022F](#) [9036F](#) [9066](#) [9047](#) [9303](#) [9318F](#) [9053](#) [9038](#) [9022](#) [9032F](#)
[9044](#) [9068F](#) [9322](#) [9033](#) [9042](#) [9043](#) [9051](#) [9030](#) [9310](#) [9058F](#) [9082](#) [9041](#) [9085](#) [9083](#) [9074F](#) [9020F](#) [9032H](#)