

1

2

3

4

5

6

7

A

B

C

D

E

F

G

H

A

B

C

D

E

F

G


H

Material

Contact(metal housing): Brass Stamped (CuZn).
 Terminal screw: Steel Zinc plating "-"slot type
 Wire guard: Stainless steel
 Insulator body(housing): Thermoplastic(UL94V-0)


Electrical

cULus

Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 14-22
 Stranded wire(AWG): 14-22
 Torque(Lb-In): 3.5
 Screw: M3
 Wire strip length: 6-7mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Safety Approval: 

N=Number of contact

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	03.01.2007	Hellwig	ASSMANN WSW-No. A-TB500-VGxxSB
X.	±0.50					Approved	29.07.2009	Hellwig	
X.X	±0.30								
X.XX	±0.10								
DIM	TOL	②	Redraw	29.07.2009	Dean			Drawing-No.	ASS 0750 CO rev02
X.°	±1°	①	Drawn	03.01.2007	Hellwig				
X.X°	±X°	①	Drawn	03.01.2007	Hellwig				
Angle	TOL	Id.	Modification	Date	Name	Replace		Sheet	

1

2

3

4

5

6

7

svxxxx