


**.300 Flanged Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
4	X			B	✓	✓	5000	50213	
		X		B	✓	✓	4000	50213-8	
			X	B	✓	*	4000	50213-8A	
	X			W	✓	✓	5000	50214	
		X		W	✓	✓	4000	50214-8	
			X	W	✓	*	4000	50214-8A	
6	X			B	✓	✓	5000	50225	
		X		B	✓	✓	4000	50225-8	
			X	B	✓	*	4000	50225-8A	
	X			W	✓	✓	5000	50226	
		X		W	✓	✓	4000	50226-8	
			X	W	✓	*	4000	50226-8A	
8	X			B	✓	✓	5000	50237	
		X		B	✓	✓	4000	50237-8	
			X	B	✓	*	4000	50237-8A	
	X			W	✓	✓	5000	50238	
		X		W	✓	✓	4000	50238-8	
			X	W	✓	*	4000	50238-8A	
10	X			B	✓	✓	5000	50249	
		X		B	✓	✓	4000	50249-8	
			X	B	✓	*	4000	50249-8A	
	X			W	✓	✓	5000	50250	
		X		W	✓	✓	4000	50250-8	
			X	W	✓	*	4000	50250-8A	

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.

**G
N
I
R
&
E
D
A
S
P
A
D
E
&
R
I
N
G
S**