

SPECIFICATIONS				
PARAMETERS	VALUES	UNITS		
RATED INPUT POWER	0.15	W		
MAX INPUT POWER	0.20	W		
IMPEDANCE	8 ± 20%	OHM		
OUTPUT SPL @ 0.1W/0.5M	72 ± 3	dBA		
(AT 1.0, 1.2, 1.4, 1.6 kHz)	7213	UDA		
DISTORTION (MAX.)	7%	-		
RESONANT FREQUENCY	1,400 ± 20%	Hz		
FREQUENCY RANGE	500 ~ 20,000	Hz		
HOUSING MATERIAL	NORYL	ORYL -		
CONE MATERIAL	MYLAR	-		
MAGNET MATERIAL	Nd-Fe-B	-		
OPERATING TEMPERATURE	-40 ~ +70	°C		
WEIGHT	10	grams		

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

©2003, Projects Unlimited Inc.

'	REVISION HISTORY				
	LTR	DESCRIPTION	DATE	APPROVED	
	-	RELEASED FROM ENGINEERING	6/9/2004		
	Α	ADDED LEAD FREE NOTE	9/22/2004	R.W.	
	В	REMOVED LEAD FREE NOTE ADDED ROHS NOTE	8/10/2005	R.W.	
	С	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	10/23/2008	B.R.	
	D	ADDED NOTE 5	1/5/2011	B.R.	







NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.

2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.

3. PIN IS TIN-PLATED RED COPPER.

4. THIS PART IS RoHS 2002/95/EC COMPLIANT.

5. HAND SOLDER ONLY.

UNLESS OTHERWISE
SPECIFIED:
DIMENSIONS ARE IN
MILLIMETERS,
TOLERANCES
ARE ±0.5 AND
ANGLES ARE ±3°.

AST-03008MR-R.idw

R.A.C. 6/9/2004

Pul
audio
nc
a projects unlimited company

Date

Designed by

 Checked by
 Date
 Approved by
 Date
 Drawn Date

 R.W.
 6/9/2004
 10/23/2008

AST-03008MR-R

Speaker Edition Sheet - 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PUI Audio: