

**CPU-1454**

**CELERON 400MHZ FANLESS SBC WITH GIGABIT & FAST ETHERNET (ROHS)**

**Features**

**Architecture:**

PC/104-Plus compliant

**Processor:**

Intel® Celeron® 400MHz, 256KB L2 cache, 100MHz FSB

**Chipset:**

Intel® 815E

**Memory:**

256MB SDRAM soldered onboard

**Supported Operating Systems:**

WinCE®, WinXPE® and Linux®

**BIOS Flash:**

1MB Flash EPROM

**Interfaces:**

- IDE Controller Ultra ATA
- Serial ports:
  - 1x RS-232
  - 1x RS-232/422/485
- 4x USB 1.1 ports
- Gigabit Ethernet (Intel® 82541PI chipset)
- Fast Ethernet (Intel® 82562ET chipset)
- Video Controllers:
  - Analog VGA output
  - Digital LVDS output
- Auxiliary Power
- AC97
- Keyboard and Mouse

**Bus:**


- PC/104-Plus (PCI)
- PC/104 (ISA)

**Watchdog:**

2-255 seconds / minutes

**Power Supply:**

Single +5V DC



**General Description**

The CPU-1454 is an embedded RoHS compliant board based on two modules: a mezzanine CPU module combined with a PC/104-Plus form factor carrier.

The mezzanine CPU module features the processor and its Intel® 815E chipset with 100MHz bus frequency. The processor is the Intel® Celeron® 400MHz 0.13µm that has low power consumption making it ideal for embedded applications. The system comes with 256MB SDRAM soldered onboard. No active cooling is required to operate within the standard and extended temperature ranges. The carrier implements all the connections to the external world, including 4 USB ports, 1 Gigabit Ethernet interface (1000Mbps), Ethernet 10/100Mbps, Analog VGA and Digital LVDS outputs, 2 Serial ports, 1 AC97 audio interface, Auxiliary Power, Keyboard and Mouse connectors and an IDE controller that supports any type of IDE Flash devices (Disk-On-Module, Compact Flash and Flash Disk). The carrier also performs the connections for the ISA and PCI bus enabling the CPU-1454 to stack on top of a PC/104-Plus system. The carrier provides support for Watchdog management and Real Time Clock (external backup battery) and can be customized to match specific customer needs.

The BIOS for the module is embedded and is located in a 1MB Flash EPROM, it is fully re-programmable onboard. The set-up parameters are saved in Flash to allow the module to operate without a battery.

## Embedded Enhanced BIOS

- The Eurotech BIOS with enhanced embedded features can be easily customized and upgraded to match the specific system configuration.
- Watchdog management.
- Set-Up in Flash in order to avoid Set-Up corruption in field.
- Virtual Peripheral Support (V.P.S.): this mode allows users to bootstrap from the parallel or serial ports and also redirect Keyboard, Video and Floppy Disk on the serial/parallel ports before booting the Operating System. It is also possible to redirect any of these peripherals as default setting.
- Etherboot support: this feature allows the system to boot up from a LAN connection for diskless operation.

## Physical Characteristics

- **Dimensions:** 90 x 96 mm (3.6" X 3.8")
- **Height:** 18.6 mm (0.7")
- **Power supply:** Single +5V DC +/- 5%
- **Power consumption:** 8.0 W typical
- **Operating Temperature:** 0 ~ + 50 °C (standard)  
-40 ~ +85 °C (extended)
- **Humidity:** Up to 95% non-condensing

## Options

- Custom BIOS with embedded features
- Extended operating temperature range
- Custom carrier
- Conformal coating
- Custom Connectors

## Accessories

- RJ45 10/100 Ethernet adapter
- RJ45 Gigabit Ethernet adapter
- AC97 adapter
- USB adapters
- 2mm to 2.54mm IDE cable
- Cable Set Kit
- Development Kit

## Power Management

- Temperature monitor with hardware thermal management circuit
- Power fail NMI (safe operation between 4.75V and 5.25V)



Tel. +39 0433 485 411

E-mail: [sales@eurotech.it](mailto:sales@eurotech.it)

Fax. +39 0433 485 499

URL: [www.eurotech.it](http://www.eurotech.it)

**Note.** The information in this document is subject to change without notice and should not be construed as a commitment by EuroTech S.p.A. While reasonable precautions have been taken, EuroTech S.p.A. assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eurotech:](#)

[CPU-1454-01](#)