
Buy One or Buy Bulk&SAVE

OFSP Optical Fiber Splice Protector





Specifications:

- Material: Outer Tube: Heat Shrink 3:1 Ratio Polyolefin Inner Tube: PE Copolymer Adhesive
- Color: Clear
- · ROD:OFSP-SS; ROFSP- Ceramic

Features:

- · Provides excellent protection for fiber optic splices
- The hot-melt inner tube bonds to the fiber and the heat shrinkable outer tube to encapsulate the fusion splice joint
- Provides vibration damping and an environmental seal, protecting fibers from damage and contaminants
- · The stainless steel/ceramic strength member provides additional rigidity
- ROFSP is for ribbon or flat fiber splice protection
- OFSP-08 is small for space-saving miniature splice protection


| | A Nominal Sleeve Length | | B Inner Tube Ø | | C Nominal Rod Ø | | D Recovered Ø | | | Bulk |
|-------------|-------------------------|------|----------------|-----------|-----------------|-----------|---------------|-----------|--------------|--------------|
| Item No. | In | mm | In | mm | In | mm | In | mm | Pack Qty. | Pack Qty. |
| OFSP-10-25 | 0.984 | 25.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-10-30 | 1.181 | 30.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-10-35 | 1.378 | 35.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-10-40 | 1.575 | 40.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-10-45 | 1.772 | 45.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-10-61 | 2.402 | 61.0 | 0.059 | 1.5 | 0.039 | 1.0 | 0.094 | 2.4 | 1 | 100 |
| OFSP-15-40 | 1.575 | 40.0 | 0.059 | 1.5 | 0.059 | 1.5 | 0.110 | 2.8 | 1 | 100 |
| OFSP-15-61 | 2.402 | 61.0 | 0.059 | 1.5 | 0.059 | 1.5 | 0.110 | 2.8 | 1 | 100 |
| OFSP-08-25 | 0.984 | 25.0 | 0.059 | 1.5 | 0.031 | 0.8 | 0.063 | 1.6 | 1 | 100 |
| OFSP-08-40 | 1.575 | 40.0 | 0.020 | 0.5 | 0.031 | 0.8 | 0.063 | 1.6 | 1 | 100 |
| ROFSP-40-40 | 1.575 | 40.0 | 0.142 x 0.039 | 3.6 x 1.0 | 0.157 x 0.071 | 4.0 x 1.8 | 0.197 x 0.118 | 5.0 x 3.0 | 1 | 100 |

OFST

Fiber Splice Tray System



All Periphery Holes: Ø2.8mm



OFST-1-L Splice Tray Lid

Specifications:

· Color: See Chart

Features:

- Lid, trays, and hinges are sold separately or in a kit: OFST-A-P-1
- Stackable to any number of trays
- Inter-tray fiber routing possible through slots along one of the long sides of the tray
- Color coded hinges indicate side of tray to open from. Part numbers are OFSTH-1-RED and OFSTH-1-GRN.
- Can be used with OFSH splice holders, OFSP splice protectors and OFBLT bend limiting tubing
- 3 mounting holes go through the lid and trays

OFST-1-P Splice Tray with Basic Storage Facility

OFST-1-M Splice Tray with Radius Control and Fiber Storage Elements

| No. | Color | Description | Qty. |
|-------------|-------|--|------|
| OFST-1-L | Black | Splice Tray Lid | 10 |
| OFST-1-M | Black | Splice Tray Managed with Radius Control & Dark Fiber Storage | 10 |
| OFST-1-P | Black | Splice Tray Plain with Basic Storage Facility | 10 |
| OFST-A-P-1 | Black | 1 x OFST-1-L, 1 x OFST-1-P, 2 x OFSTH-1-RED, 2 x OFSTH-1-GRN | 10 |
| OFSTH-1-GRN | Green | OF Splice Tray Hinge | 20 |
| OFSTH-1-RED | Red | OF Splice Tray Hinge | 20 |
| | | | |

EFA04-25-001 Splice Tray


Specifications:

Material: UL94 V-0 Nylon 6

· Color: Black

Features:

- Molded-in features maintain bend radius at 30mm
- Accepts Fiber Clips EFA04-61, 63 and 64-001
- Accepts 16-way Fiber Clip EFA04-06 and 08-001 broken into a 4-way segment for holding splicing components
- An Egide/Richco product



| | Lx | : W | Thickness | | Bulk |
|--------------|---------------|--------------|-----------|-----|-----------|
| Item No. | | mm | In | mm | Pack Qtv. |
| EFA04-25-001 | 5.197 x 3.228 | 132.0 x 82.0 | 0.260 | 6.6 | 50 |