



General Description

- Trench Power AlphaMOS-II technology
- Low $R_{DS(ON)}$
- Low C_{iss} and C_{rss}
- High Current Capability
- RoHS and Halogen Free Compliant



Applications

- General Lighting for LED and CCFL
- AC/DC Power supplies for Industrial, Consumer, and Telecom

Product Summary

| | |
|----------------------|----------------|
| $V_{DS} @ T_{j,max}$ | 700V |
| I_{DM} | 40A |
| $R_{DS(ON),max}$ | < 0.7 Ω |
| $Q_{g,typ}$ | 26nC |
| $E_{oss} @ 400V$ | 3.5 μ J |

100% UIS Tested
100% R_g Tested



| Orderable Part Number | Package Type | Form | Minimum Order Quantity |
|-----------------------|-----------------|-------------|------------------------|
| AOT10T60PL | TO-220 Green | Tube | 1000 |
| AOB10T60PL | TO-263 Green | Tape & Reel | 800 |
| AOTF10T60P | TO-220F Pb Free | Tube | 1000 |
| AOTF10T60PL | TO-220F Green | Tube | 1000 |

Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter | Symbol | AOT(B)10T60P | AOTF10T60P | AOTF10T60PL | Units | |
|--|----------------|---------------------------------|------------|-------------|------------------|---------------------|
| Drain-Source Voltage | V_{DS} | 600 | | | V | |
| Gate-Source Voltage | V_{GS} | ± 30 | | | V | |
| Continuous Drain Current | I_D | $T_C=25^\circ\text{C}$ | 10 | 10* | A | |
| | | $T_C=100^\circ\text{C}$ | 6.6 | 6.6* | | |
| Pulsed Drain Current ^C | I_{DM} | 40 | | | | |
| Avalanche Current ^C $L=1\text{mH}$ | I_{AR} | 10 | | | A | |
| Repetitive avalanche energy ^C | E_{AR} | 50 | | | mJ | |
| Single pulsed avalanche energy ^G | E_{AS} | 480 | | | mJ | |
| MOSFET dv/dt ruggedness | dv/dt | 50 | | | V/ns | |
| Peak diode recovery dv/dt ^J | | 15 | | | | |
| Power Dissipation ^B | P_D | $T_C=25^\circ\text{C}$ | 208 | 43 | 33 | W |
| | | Derate above 25°C | 1.7 | 0.3 | 0.26 | W/ $^\circ\text{C}$ |
| Junction and Storage Temperature Range | T_J, T_{STG} | -55 to 150 | | | $^\circ\text{C}$ | |
| Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds | T_L | 300 | | | $^\circ\text{C}$ | |

Thermal Characteristics

| Parameter | Symbol | AOT(B)10T60P | AOTF10T60P | AOTF10T60PL | Units |
|--|-----------------|--------------|------------|-------------|---------------------------|
| Maximum Junction-to-Ambient ^{A,D} | $R_{\theta JA}$ | 65 | 65 | 65 | $^\circ\text{C}/\text{W}$ |
| Maximum Case-to-sink ^A | $R_{\theta CS}$ | 0.5 | -- | -- | $^\circ\text{C}/\text{W}$ |
| Maximum Junction-to-Case | $R_{\theta JC}$ | 0.6 | 2.9 | 3.8 | $^\circ\text{C}/\text{W}$ |

* Drain current limited by maximum junction temperature.

Electrical Characteristics (T_J=25°C unless otherwise noted)

| Symbol | Parameter | Conditions | Min | Typ | Max | Units | |
|------------------------------------|---|---|-----|------|------|-------|----|
| STATIC PARAMETERS | | | | | | | |
| BV _{DSS} | Drain-Source Breakdown Voltage | I _D =250μA, V _{GS} =0V, T _J =25°C | 600 | | | V | |
| | | I _D =250μA, V _{GS} =0V, T _J =150°C | | 700 | | | |
| BV _{DSS} /ΔT _J | Breakdown Voltage Temperature Coefficient | I _D =250μA, V _{GS} =0V | | 0.56 | | V/°C | |
| I _{DSS} | Zero Gate Voltage Drain Current | V _{DS} =600V, V _{GS} =0V | | | 1 | μA | |
| | | V _{DS} =480V, T _J =125°C | | | 10 | | |
| I _{GSS} | Gate-Body leakage current | V _{DS} =0V, V _{GS} =±30V | | | ±100 | nA | |
| V _{GS(th)} | Gate Threshold Voltage | V _{DS} =5V, I _D =250μA | 3 | 4.3 | 5 | V | |
| R _{DS(ON)} | Static Drain-Source On-Resistance | V _{GS} =10V, I _D =5A | | 0.58 | 0.7 | Ω | |
| g _{FS} | Forward Transconductance | V _{DS} =40V, I _D =5A | | 8.8 | | S | |
| V _{SD} | Diode Forward Voltage | I _S =1A, V _{GS} =0V | | 0.74 | 1 | V | |
| I _S | Maximum Body-Diode Continuous Current | | | | 10 | A | |
| I _{SM} | Maximum Body-Diode Pulsed Current ^C | | | | 40 | A | |
| DYNAMIC PARAMETERS | | | | | | | |
| C _{iss} | Input Capacitance | V _{GS} =0V, V _{DS} =100V, f=1MHz | | 1595 | | pF | |
| C _{oss} | Output Capacitance | | | | 56 | | pF |
| C _{o(er)} | Effective output capacitance, energy related ^H | V _{GS} =0V, V _{DS} =0 to 480V, f=1MHz | | 42 | | pF | |
| C _{o(tr)} | Effective output capacitance, time related ^I | | | | 74 | | pF |
| C _{rss} | Reverse Transfer Capacitance | V _{GS} =0V, V _{DS} =100V, f=1MHz | | 11 | | pF | |
| R _g | Gate resistance | f=1MHz | | 1.7 | | Ω | |
| SWITCHING PARAMETERS | | | | | | | |
| Q _g | Total Gate Charge | V _{GS} =10V, V _{DS} =480V, I _D =10A | | 26 | 40 | nC | |
| Q _{gs} | Gate Source Charge | | | 8.1 | | | nC |
| Q _{gd} | Gate Drain Charge | | | 8.2 | | | nC |
| t _{D(on)} | Turn-On DelayTime | V _{GS} =10V, V _{DS} =300V, I _D =10A, R _G =25Ω | | 42 | | ns | |
| t _r | Turn-On Rise Time | | | 54 | | ns | |
| t _{D(off)} | Turn-Off DelayTime | | | 52 | | ns | |
| t _f | Turn-Off Fall Time | | | 24 | | ns | |
| t _{rr} | Body Diode Reverse Recovery Time | I _F =10A, di/dt=100A/μs, V _{DS} =100V | | 497 | | ns | |
| Q _{rr} | Body Diode Reverse Recovery Charge | I _F =10A, di/dt=100A/μs, V _{DS} =100V | | 7.3 | | μC | |

A. The value of R_{θJA} is measured with the device in a still air environment with T_A=25°C.

B. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and duty cycles to keep initial T_J=25°C.

D. The R_{θJA} is the sum of the thermal impedance from junction to case R_{θJC} and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300 ms pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T_{J(MAX)}=150°C. The SOA curve provides a single pulse rating.

G. L=60mH, I_{AS}=4A, V_{DD}=150V, R_G=25Ω, Starting T_J=25°C.

H. C_{o(er)} is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% V_{(BR)DSS}.

I. C_{o(tr)} is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% V_{(BR)DSS}.

J. I_{SD}≤I_D, di/dt≤200A/μs, V_{DD}=400V, T_J≤T_{J(MAX)}.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Break Down vs. Junction Temperature








Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 11: Maximum Forward Biased Safe Operating Area for TO-220/TO-263 (Note F)




Figure 12: Maximum Forward Biased Safe Operating Area for TO-220F Pb Free (Note F)




Figure 13: Maximum Forward Biased Safe Operating Area for TO-220F Green (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 14: Normalized Maximum Transient Thermal Impedance for TO-220/TO-263 (Note F)




Figure 15: Normalized Maximum Transient Thermal Impedance for TO-220F Pb Free (Note F)








Figure 16: Normalized Maximum Transient Thermal Impedance for TO-220F Green (Note F)



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

