


**G
N
I
R
&
E
D
A
S**

Spade and Ring Series Pre-Insulated


**.240 Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)**



STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.117	.147	.180					
		X			B	✓	✓	5000	50001
			X		B	✓	✓	4000	50001-8
				X	B	✓	*	4000	50001-8A
	0	X			W	✓	✓	5000	50002
			X		W	✓	✓	4000	50002-8
				X	W	✓	*	4000	50002-8A
		X			B	✓	✓	5000	50009
			X		B	✓	✓	4000	50009-8
				X	B	✓	*	4000	50009-8A
	2	X			W	✓	✓	5000	50010
			X		W	✓	✓	4000	50010-8
				X	W	✓	*	4000	50010-8A
		X			B	✓	✓	5000	50017
			X		B	✓	✓	4000	50017-8
				X	B	✓	*	4000	50017-8A
	4	X			W	✓	✓	5000	50018
			X		W	✓	✓	4000	50018-8
				X	W	✓	*	4000	50018-8A
		X			B	✓	✓	5000	50025
			X		B	✓	✓	4000	50025-8
				X	B	✓	*	4000	50025-8A
	6	X			W	✓	✓	5000	50026
			X		W	✓	✓	4000	50026-8
				X	W	✓	*	4000	50026-8A

Spade and Ring Series Pre-Insulated

**.300 Spade
.020 Pre-Tinned Brass
22-18 AWG (Red)**



STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.117	.147	.180					
		X			B	✓	✓	5000	50165-200
	4		X		B	✓	✓	4000	50165-200-8
				X	B	✓	*	4000	50165-200-8A
		X			B	✓	✓	5000	50177-200
	6		X		B	✓	✓	4000	50177-200-8
				X	B	✓	*	4000	50177-200-8A
		X			B	✓	✓	5000	50189-200
	8		X		B	✓	✓	4000	50189-200-8
				X	B	✓	*	4000	50189-200-8A
		X			B	✓	✓	5000	50201-200
	10		X		B	✓	✓	4000	50201-200-8
				X	B	✓	*	4000	50201-200-8A

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.