


**.300 Ring
.040 Electro-Tinned Copper
12-10 AWG (Yellow)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.207	.260	.300						
4	X			B	✓	✓	2500	50317	
		X		B	✓	✓	2000	50317-8	
			X	B	✓	*	2000	50317-8A	
	X			W	✓	✓	2500	50318	
		X		W	✓	✓	2000	50318-8	
			X	W	✓	*	2000	50318-8A	
6	X			B	✓	✓	2500	50329	
		X		B	✓	✓	2000	50329-8	
			X	B	✓	*	2000	50329-8A	
	X			W	✓	✓	2500	50330	
		X		W	✓	✓	2000	50330-8	
			X	W	✓	*	2000	50330-8A	
8	X			B	✓	✓	2500	50356	
		X		B	✓	✓	2000	50356-8	
			X	B	✓	*	2000	50356-8A	
	X			W	✓	✓	2500	50357	
		X		W	✓	✓	2000	50357-8	
			X	W	✓	*	2000	50357-8A	
10	X			B	✓	✓	2500	50368	
		X		B	✓	✓	2000	50368-8	
			X	B	✓	*	2000	50368-8A	
	X			W	✓	✓	2500	50369	
		X		W	✓	✓	2000	50369-8	
			X	W	✓	*	2000	50369-8A	

Recommended Strip Length $\frac{5}{16} \pm \frac{3}{64}$

* Contact Factory for Latest Agency Approvals

**S
P
A
D
&
R
I
N
G**