

Number of contacts

64



Female connectors

DIN Signal to 2 A

Identification	Number of contacts	Part No.	Drawing	Dimensions in mm
Female connector for insulation displacement	64	Performance level 2 ¹⁾ 09 03 264 6828 09 03 764 6828 ^{c)}		
Strain relief		Performance level 3 ¹⁾ 09 03 264 7828		
Panel cut out		09 03 000 9940		<p>Cable 1 to contact 1 c</p> <p>Contact arrangement View from termination side</p>
Flat cable				<p>Mateable with 3 row male connector type C, no female contacts in the middle row</p> <p>²⁾ Termination area spacing = 508 mm</p> <p>Important: always store reels vertically</p> <p>Wire (tinned) Cu Gauge AWG 28/7 0.089 mm² Insulation material as per UL style PVC</p>
Round flat cable ³⁾				<p>³⁾ Termination area spacing = 100 mm</p>
Bench press		09 99 000 0114		
Base plate		09 99 000 0150		
Cable cutter		09 99 000 0116		
Spare parts				
Blade		09 99 000 0179		
Cutting plate		09 99 000 0180		



Further components and accessories for insulation displacement see interface catalogue, chapter 40

^{c)} Connectors with coding see page 01.44

¹⁾ acc. to IEC 60 603-2