


MALE PCB PINS

PRINTED CIRCUIT PINS

0259/0286/1941

XXXX-0-00-XX-00-00-03-0

Press-fit in .057/.059 mounting hole




Basic Part Number	Length L	Barb Dia. E	Mounting Hole
0259-0	.173	.062	.059
0286-0	.115	.060	.057
1941-0	.169	.058	.056

2956-0

2956-0-00-XX-00-00-03-0


Surface mount



2956-1

2956-1-00-XX-00-00-03-0


Surface mount



4956-1

4956-1-00-XX-00-00-33-0


Surface mount



8876

8876-0-00-XX-00-00-03-0


Press-fit in .057 mounting hole



1938

1938-0-00-XX-00-00-03-0


Press-fit in .057 mounting hole



1940

1940-0-00-XX-00-00-03-0


Press-fit in .057 mounting hole



1942

1942-0-00-XX-00-00-03-0

Press-fit in .057 mounting hole




3024

3024-0-01-XX-00-00-03-0

Press-fit in .057 mounting hole

For wire sizes up to 22 AWG




1107

1107-0-01-15-00-00-03-0

Press-fit in .057 mounting hole


For wire sizes up to 20 AWG



3000

3000-0-00-XX-00-00-03-0

Press-fit in .061 mounting hole. Accepts wire sizes 24 AWG Max. / 28 AWG Min.



SPECIFICATIONS:

Pin Material: Brass Alloy 360, 1/2 Hard
(Except swage pins which are annealed)

Dimensions: Inches

Tolerances On: Lengths: ±.005
Diameters: ±.002
Angles: ±2°



ORDER CODE: **XXXX - X - 0X - XX - 00 - 00 - XX - 0**

BASIC PART #

SPECIFY PIN FINISH:

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)
- ◆ 21 20 μ" GOLD OVER NICKEL (RoHS)
- ◆ 34 50 μ" GOLD OVER NICKEL (RoHS)

