



1) Einlotstifte passend für Lochungen $\phi 1 \pm 0,1$ nach IEC 60326-3
 Solder pins for PCB connections $\phi 1 \pm 0,1$ as per IEC 60326-3
 A souder pour des trous de $\phi 1 \pm 0,1$ selon IEC 60326-3

A	09195067321	3	4,5							 All Dim. in mm Orig. Size DIN A 4	SEK 19 Male connector 6 poles, low profile, high temperature with angled pins	Maßstab/ Scale 1.5:1
	09195066321	2	4,5				Detail.	25-APR-02	CV			
	09195065321	0.76 $\mu\text{m Au}$	4,5				Insp.					
	09195067323	3	2,9				Stand.					
	09195066323	2	2,9									
	09195065323	0.76 $\mu\text{m Au}$	2,9	29778	25-APR-02	CV						
	Part-No.	performance level	a	Mod.	Dat.	Name	HARTING EURL F-95972 Paris				TB 0919506x32x Sub.	Blatt/ Page 2 / 2

09 19 506 6323
IDC male connector

Other applications

Connector size	6 contacts
Termination	Angled solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	Performance level 2

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)

09 19 506 7323
IDC male connector

Other applications

Connector size	6 contacts
Termination	Angled solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	Performance level 3

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)

09 19 506 5323
IDC male connector

Other applications

Connector size	6 contacts
Termination	Angled solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	AU-0.76 μ m [30 μ Inch]

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)