



## N-Channel Enhancement-Mode Vertical DMOS FET

### Features

- ▶ Low threshold (1.6V max.)
- ▶ High input impedance
- ▶ Low input capacitance
- ▶ Fast switching speeds
- ▶ Low on-resistance
- ▶ Free from secondary breakdown
- ▶ Low input and output leakage

### Applications

- ▶ Logic level interfaces – ideal for TTL and CMOS
- ▶ Solid state relays
- ▶ Battery operated systems
- ▶ Photo voltaic drives
- ▶ Analog switches
- ▶ General purpose line drivers
- ▶ Telecom switches

### General Description

This low threshold, enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven, silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

### Ordering Information

Device	Package Options		Wafer / Die Options		
	TO-92	TO-243AA (SOT-89)	NW (Die in wafer form)	NJ (Die on adhesive tape)	ND (Die in waffle pack)
TN0104	TN0104N3-G	TN0104N8-G	TN1504NW	TN1504NJ	TN1504ND

For packaged products, -G indicates package is RoHS compliant ('Green'). Devices in Wafer / Die form are RoHS compliant ('Green'). Refer to Die Specification VF15 for layout and dimensions.

### Product Summary


Device	$BV_{DSS}/BV_{DGS}$ (V)	$R_{DS(ON)}$ (max) ( $\Omega$ )	$I_{D(ON)}$ (min) (A)	$V_{GS(th)}$ (max) (V)
TN0104N3-G	40	1.8	2.0	1.6
TN0104N8-G	40	2.0	2.0	1.6

### Absolute Maximum Ratings

Parameter	Value
Drain-to-source voltage	$BV_{DSS}$
Drain-to-gate voltage	$BV_{DGS}$
Gate-to-source voltage	$\pm 20V$
Operating and storage temperature	-55°C to +150°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

### Pin Configurations



### Product Marking



YY = Year Sealed  
WW = Week Sealed  
\_\_\_\_\_ = "Green" Packaging

Package may or may not include the following marks: Si or

TO-92 (N3)



W = Code for Week Sealed  
\_\_\_\_\_ = "Green" Packaging

Package may or may not include the following marks: Si or

TO-243AA (SOT-89) (N8)

## Thermal Characteristics

Package	$I_D$ (continuous) <sup>t</sup> (mA)	$I_D$ (pulsed) (A)	Power Dissipation @ $T_c = 25^\circ\text{C}$ (W)	$\theta_{jc}$ (°C/W)	$\theta_{ja}$ (°C/W)	$I_{DR}^t$ (mA)	$I_{DRM}$ (A)
TO-92	450	2.40	1.0	125	170	450	2.40
TO-243AA (SOT-89)	630	2.90	1.6 <sup>#</sup>	15	78 <sup>#</sup>	630	2.90

Notes:

<sup>t</sup>  $I_D$  (continuous) is limited by max rated  $T_j$ .

<sup>#</sup>  $T_A = 25^\circ\text{C}$ . Mounted on FR5 Board, 25mm x 25mm x 1.57mm. Significant  $P_D$  increase possible on ceramic substrate.



## Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Sym	Parameter	Min	Typ	Max	Units	Conditions
$BV_{DSS}$	Drain-to-source breakdown voltage	40	-	-	V	$V_{GS} = 0\text{V}$ , $I_D = 1.0\text{mA}$
$V_{GS(\text{th})}$	Gate threshold voltage	0.6	-	1.6	V	$V_{GS} = V_{DS}$ , $I_D = 500\mu\text{A}$
$\Delta V_{GS(\text{th})}$	Change in $V_{GS(\text{th})}$ with temperature	-	-3.8	-5.0	mV/°C	$V_{GS} = V_{DS}$ , $I_D = 1.0\text{mA}$
$I_{GSS}$	Gate body leakage	-	0.1	100	nA	$V_{GS} = \pm 20\text{V}$ , $V_{DS} = 0\text{V}$
$I_{DSS}$	Zero gate voltage drain current	-	-	1.0	$\mu\text{A}$	$V_{GS} = 0\text{V}$ , $V_{DS}$ = Max Rating
		-	-	100		$V_{DS} = 0.8$ Max Rating, $V_{GS} = 0\text{V}$ , $T_A = 125^\circ\text{C}$
$I_{D(\text{ON})}$	On-state drain current	-	0.35	-	A	$V_{GS} = 3.0\text{V}$ , $V_{DS} = 20\text{V}$
		0.5	1.1	-		$V_{GS} = 5.0\text{V}$ , $V_{DS} = 20\text{V}$
		2.0	2.6	-		$V_{GS} = 10\text{V}$ , $V_{DS} = 20\text{V}$
$R_{DS(\text{ON})}$	Static drain-to-source on-state resistance	-	5.0	-	$\Omega$	$V_{GS} = 3.0\text{V}$ , $I_D = 50\text{mA}$
		-	2.3	2.5		$V_{GS} = 5.0\text{V}$ , $I_D = 250\text{mA}$
		TO-92	-	1.5		$V_{GS} = 10\text{V}$ , $I_D = 1.0\text{A}$
		TO-243AA	-	-		
$\Delta R_{DS(\text{ON})}$	Change in $R_{DS(\text{ON})}$ with temperature	-	0.7	1.0	%/°C	$V_{GS} = 10\text{V}$ , $I_D = 1.0\text{A}$
$G_{FS}$	Forward transductance	340	450	-	mmho	$V_{DS} = 20\text{V}$ , $I_D = 500\text{mA}$
$C_{ISS}$	Input capacitance	-	-	70	pF	$V_{GS} = 0\text{V}$ , $V_{DS} = 20\text{V}$ , $f = 1.0\text{MHz}$
$C_{OSS}$	Common source output capacitance	-	-	50		
$C_{RSS}$	Reverse transfer capacitance	-	-	15		
$t_{d(\text{ON})}$	Turn-on delay time	-	3.0	5.0	ns	$V_{DD} = 20\text{V}$ , $I_D = 1.0\text{A}$ , $R_{GEN} = 25\Omega$
$t_r$	Rise time	-	7.0	8.0		
$t_{d(\text{OFF})}$	Turn-off delay time	-	6.0	9.0		
$t_f$	Fall time	-	5.0	8.0		
$V_{SD}$	Diode forward voltage drop	TO-92	-	1.2	V	$V_{GS} = 0\text{V}$ , $I_{SD} = 1.0\text{A}$
		TO-243AA	-	-		$V_{GS} = 0\text{V}$ , $I_{SD} = 0.5\text{A}$
$t_{rr}$	Reverse recovery time	-	300	-	ns	$V_{GS} = 0\text{V}$ , $I_{SD} = 1.0\text{A}$







Notes:

- All D.C. parameters 100% tested at  $25^\circ\text{C}$  unless otherwise stated. (Pulse test: 300μs pulse, 2% duty cycle.)
- All A.C. parameters sample tested.







## Switching Waveforms and Test Circuit






## Typical Performance Curves



## Typical Performance Curves (cont.)



## 3-Lead TO-92 Package Outline (N3)



Symbol		A	b	c	D	E	E1	e	e1	L
Dimensions (inches)	MIN	.170	.014 <sup>†</sup>	.014 <sup>†</sup>	.175	.125	.080	.095	.045	.500
	NOM	-	-	-	-	-	-	-	-	-
	MAX	.210	.022 <sup>†</sup>	.022 <sup>†</sup>	.205	.165	.105	.105	.055	.610*

JEDEC Registration TO-92.


\* This dimension is not specified in the JEDEC drawing.

† This dimension differs from the JEDEC drawing.


Drawings not to scale.

Supertex Doc.#: DSPD-3TO92N3, Version E041009.

## 3-Lead TO-243AA (SOT-89) Package Outline (N8)



**Top View**



**Side View**

Symbol	A	b	b1	C	D	D1	E	E1	e	e1	H	L	
Dimensions (mm)	MIN	1.40	0.44	0.36	0.35	4.40	1.62	2.29	2.00 <sup>t</sup>	1.50 BSC	3.00 BSC	3.94	0.73 <sup>t</sup>
	NOM	-	-	-	-	-	-	-	-			-	-
	MAX	1.60	0.56	0.48	0.44	4.60	1.83	2.60	2.29			4.25	1.20

JEDEC Registration TO-243, Variation AA, Issue C, July 1986.

<sup>t</sup> This dimension differs from the JEDEC drawing

*Drawings not to scale.*

Supertex Doc. #: DSPD-3TO243AAN8, Version F111010.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

**Supertex inc.** does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: <http://www.supertex.com>)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Supertex:

[TN0104N3-G](#) [TN0104N8-G](#) [TN0104N3-G P003](#) [TN0104N3-G P014](#) [TN0104N3-G P002](#) [TN0104N3-G P013](#)  
[TN0104N3-G P005](#)