



**.300 Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
4	X			B	/	/	5000	50165	
		X		B	/	/	4000	50165-8	
			X	B	/	*	4000	50165-8A	
	X			W	/	/	5000	50166	
		X		W	/	/	4000	50166-8	
			X	W	/	*	4000	50166-8A	
6	X			B	/	/	5000	50177	
		X		B	/	/	4000	50177-8	
			X	B	/	*	4000	50177-8A	
	X			W	/	/	5000	50178	
		X		W	/	/	4000	50178-8	
			X	W	/	*	4000	50178-8A	
8	X			B	/	/	5000	50189	
		X		B	/	/	4000	50189-8	
			X	B	/	*	4000	50189-8A	
	X			W	/	/	5000	50190	
		X		W	/	/	4000	50190-8	
			X	W	/	*	4000	50190-8A	
10	X			B	/	/	5000	50201	
		X		B	/	/	4000	50201-8	
			X	B	/	*	4000	50201-8A	
	X			W	/	/	5000	50202	
		X		W	/	/	4000	50202-8	
			X	W	/	*	4000	50202-8A	



Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.

**U
N
I
R
&
E
D
A
S
P
A
D
E
&
R
I
N
G**