

FIBER BEND LIMITING TUBING & SPLICE HOLDERS




OFSMB - OFBLT Slotted Multi Bracket

Specifications:

- Material: UL94 V-0 Glass-Filled Nylon
- Color: Black

Features:

- For use with 5mm OFBLT Tubing
- Mounts with #10 (M5) screws
- Optical Fiber Slotted Multi-Brackets are for use at distribution points where orderly fiber management, protection and strain relief is required
- An additional security feature allows fitting of a cable tie around OFSMBs which prevents removal of any retained tubes
- OFBLT retention: >70N
- Holds a maximum of 12 tubes



Item	Bulk Pack
No.	Qty.
OFSMB-4-05GFBK	10

OFSH-T Splice Holder


Specifications:

Material: See Chart

Color: Black

Features:

- OFSH-T-6 holds up to 6 x 3mm fiber or components, i.e. couplers and splice protectors
- OFSH-T-12 holds up to 12 crimp splice protectors
- Splice Holders can be used with OFST Series Splice Trays.






Figure 2

	1		_
-	////	//	4
	200		

Richco

Richco

Richco

Item		Ø Component			Bulk Pack	
No.	Figure	Material	ln .	mm	No. of Slots	Qty.
OFSH-T-6-GFBLK	1	Glass Filled Nylon 6/6	0.118	3.0	6	100
OFSH-T-12-01BLK	2	Nylon 6/6	0.039 - 0.047	1.0 - 1.2	6	100
OFSH-T-12-19BLK	2	Nylon 6/6	0.039 - 0.047	1.0 - 1.2	12	100

OFSH2 Splice Holder



Specifications:

- Material: UL94 V-0 Nylon 6/6
- Color: Black

- Features: Holds up to 24 components/splice protectors
- Flexible wings grip components up to .06 (1.6) in diameter
- Low profile to save space
- Two styles: one for mounting with an adhesive pad and one for mounting with a #4 or M3 screw
- Each slot holds up to two components

2.87 (73.0) Ref. RRRRRRR 1.02 REF. (26.0) Ref. (26.0)	3.21 (81.5) 0.13 (3.2)
20 (5.0) Figure 1	3.39 (86.0) Ref. Figure 2

unting Met OFSH2-24-1 Adhesive Up to 0.060 OFSH2-24-2 No Adhesive Up to 0.060 Up to 1.6 50 Up to 0.060 #4 or M3 Screws

OFSH-4 Splice Holder


Material: See Chart

Specifications:

- Color: Natural

Features:

- Holds twelve 2.7mm splices or four 4.2mm splices
- Fastens with either an adhesive pad provided, or with a #4 screw or rivet.
- Stackable



OFSH-4-1-19LA

