

0669 0670 0673 0666

0669-0-15-XX-30-XX-10-0
Solder mount in 1,52 min. mounting hole

0670-0-15-XX-30-XX-10-0
Solder mount in 1,52 min. mounting hole

0673-0-15-XX-30-XX-10-0
Surface Mount

0666-0-15-XX-32-XX-10-0
Solder mount in 1,63 min. mounting hole
Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel.
Order as: 0666-0-57-XX-32-XX-10-0

0341 0252 0678 0676

0341-0-15-XX-30-XX-10-0
Solder mount in 1,85 mounting hole
Also available on 12mm wide carrier tape: 1,400 parts per 330mm reel.
Order as: 0341-0-57-XX-30-XX-10-0

0252-0-15-XX-32-XX-10-0
Hex press-fit in 1,45 plated thru hole

0678-0-15-XX-32-XX-10-0
Press-fit in 1,45 mounting hole

0676-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

0697 0668 0253/1033

0697-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

0668-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

XXX3-0-15-XX-30-XX-10-0
Press-fit in 1,45 mounting hole

Basic Part Number	Length L	Depth N
0253-0	4,39	3,76
1033-0	5,16	4,11

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

DIMENSION IN INCHES TOLERANCES ON:
LENGTHS: ±0,13
DIAMETERS: ±0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0

BASIC PART # **SPECIFY SHELL FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◇ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◇ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 02 2,54µm TIN/LEAD OVER NICKEL
- ◇ 84 2,54µm TIN OVER NICKEL (RoHS)
- ◇ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT
#30 or #32 CONTACT (DATA ON PAGES 218 & 219)