



Minicom SmartRack 116 IP - 16-Port Remote Access Console Cat5 KVM with 17" LCD

MODEL NUMBER: 0SU70050



Description

Local and Remote Access

The SmartRack comes with a 116 IP Cat5 KVM switch for combined local and remote access. To access servers, just slide out the drawer and flip up its top to display the large, high resolution 17" TFT LCD display. The display is (VGA/SVGA/XGA/SXGA compatible) with front-panel high-quality controls and Touchpad for easy adjustment. It features triple layered security and plug-and-play installation.

Control More Servers

The SmartRack Cat5 KVM switches are compatible with all major operating systems and can control any server's brand and model, regardless of the server condition and network connectivity, covering the entire spectrum of crash scenarios. Use the KVM switch to control up to 16 servers in multiple platforms (PS/2, USB). The innovative ROC technology has each computer/ server directly connected to the switch via a ROC using standard CAT5 cable at a distance of up to 30m/100ft in a star configuration.

Slim, 1U Solution that Saves Space

The SmartRack Cat5 KVM switches are a single rail solution that occupies just 1U of rack space; it's the most efficient way to control your server rack.

SmartRack 116 IP Key features

The SmartRack 116 IP extends your KVM from any computer or server over TCP/IP via LAN, WAN or Internet connection. Now you can control, monitor and manage up to 16 remote servers from wherever you are, inside or outside the organization. The SmartRack 116 IP is a cost-effective hardware solution, for secure remote KVM access & control of 16 computers/servers from the BIOS level - independent of the OS. One local analog or one remote digital IP user can access and control 16 multi-platforms (PS/2, USB) servers at a time.

Highlights

- 16 Port KVM
- 17" TFT LCD Display
- Remote or Local Access
- BIOS level access
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cable
- Compliant with the Federal Trade Agreement (TAA) for GSA Schedule purchases

System Requirements

Operating System

- Compatible with Windows, Linux, Unix and all other major operating systems

Resolution

- Supports video resolutions up to 1280 x 1024

Package Includes

- SmartRack 116 IP Cat5 KVM Switch
- RS232 Download Cable
- Rackmount Kit
- Owner's Manual



Features

- 16 Port KVM
- 17" TFT LCD Display
- Remote or Local Access
- BIOS level access
- Multi-platform – PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cable
- Compliant with the Federal Trade Agreement (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
# Of Users	1
Port Control	Hotkeys, OSD, Remote Toolbar
PC/Server	VGA; USB; PS/2
Cat5 KVM Switch	Yes
IP Remote Access	YES, BUILT IN
Model Type	KVM Switches
UPC ASSIGNMENT	
Unit Carton UPC#	654518211351
PHYSICAL	
Unit Dimensions (hwd / in.)	1.7 x 17.6 x 25.2
Unit Dimensions (hwd / cm)	4.4 x 44.75 x 64
Unit Weight (lbs.)	40.1
Unit Weight (kg)	18.2
Color	Black
Style	1U Rackmount Console
ENVIRONMENTAL	
Storage Temperature Range	-40 to 70 C / -40 to 158 F
Relative Humidity	10 to 90% RH
Operating Temperature	0 to 40 C / 32 to 104 F
CONNECTIONS	
Ports	16



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Computer/Server Ports	16
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.