



For more  
Information  
please call

1-800-Belden1



## Description:

Small and Lightweight with a rugged jacket, Tactical Cable provides a durable design for repeated deployment and retrieval cycles and a superior level of crush resistance. Designed to military standards.

## Fiber

### Applicable Standards and Agency Compliance

#### Suitability

**Sunlight Resistance:** Yes - Black only.

## Physical Characteristics (Overall)

### Product Family - Other:

Fiber Count	OM1 - MM 62.5/125 1Gb	OM2 - MM 50/125 1Gb	OM3 - MM 50/125 10Gb 300m	OM4 - MM 50/125 10Gb 500m	OS2 -SM
2	B96571	.	.	.	B96566
4	B96551	.	.	.	B96639
6	B96572 or B96572l	.	.	.	B96567 or B96567l
8	B96573	B96568			
12	B96575 or B96575l	.	.	.	B96570 or B96570l

**Fiber Type:** SM, (OS2)

**Number of Fibers:** 4

**Buffer Tube Material:** Thermoplastic

### Outer Jacket

#### Outer Jacket Material:

<b>Outer Jacket Material</b>
PU - Polyurethane

### Strength Member

**Strength Member Material:** Aramid Yarn

### Overall Cable

**Overall Nominal Diameter:** 0.240 in.

## Mechanical Characteristics (Overall)

**Storage Temperature Range:** -70°C To +85°C

**Installation Temperature Range:** -20°C To +85°C

**Operating Temperature Range:** -55°C To +85°C

<b>Bulk Cable Weight:</b>	22 lbs/1000 ft.
<b>Min. Bend Radius/Minor Axis:</b>	3.600 in.
<b>Min. Bend Radius for Long Term Application:</b>	1.900 in.
<b>Max. Load for Installation:</b>	330 lbs.
<b>Max. Load for Long Term Application:</b>	150 lbs.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

<b>EU Directive 2000/53/EC (ELV):</b>	Yes
<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	01/19/2010
<b>EU Directive 2002/96/EC (WEEE):</b>	Yes
<b>EU Directive 2003/11/EC (BFR):</b>	Yes
<b>CA Prop 65 (CJ for Wire &amp; Cable):</b>	Yes
<b>MII Order #39 (China RoHS):</b>	Yes

### Suitability

<b>Suitability - Indoor:</b>	Yes - by exemption
<b>Suitability - Outdoor:</b>	Yes
<b>Suitability - Aerial:</b>	Yes - Black only, when supported by messenger wire.
<b>Sunlight Resistance:</b>	Yes

### Plenum/Non-Plenum

<b>Plenum (Y/N):</b>	No
----------------------	----

## Optical Characteristics (Overall)

<b>Maximum Attenuation @ 1310nm:</b>	.8 dB/km
<b>Maximum Attenuation @ 1550nm:</b>	.5 dB/km
<b>Maximum Gigabit Ethernet Length @ 1300nm:</b>	5000 meters

### Fiber Coding MLT EMEA:

Fiber/Tube No.	Color
1	Blue
2	Orange
3	Green
4	Brown
5	Gray
6	White
7	Red
8	Black
9	Yellow
10	Purple
11	Rose
12	Aqua

## Related Documents:

[Tactical\\_Cable.pdf](#) - Tactical cable technical data sheet for product family.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
B96639	1 FT	0.031 LB	BLACK		TACT 4F OS2 BLK

Revision Number: 1    Revision Date: 11-13-2012

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[B96570](#) [B96551](#) [B96567](#) [B96639](#)