Molex Connector Part Number - 0433750001

violex Connector 1 art	Number - 0433/50001	
<u> Molex.com</u>	English 日本평 한국어 简体中文	Register Login My Parts (0 items)
Product Name Cross-Ref Catalog Literature Industries Standards Contact Us About Us Investors Careers Connectors	Search site:Search: Enter Part No. or K Go	Lighting Products
witch Language English	<u>Home</u> <u>Crimp Terminals</u> Datasheet	
eed Assistance? ontact Us ind a Distributor rder Samples ech Library cocare lectrical Models	Part Number: 0433750001 Status: Active Overview: Sabre™	
Printer-friendly page	Description: Sabre™ Crimp Terminal, Female, with Tin (Sn) Plated Brass Contact, 14-16 AWG, Tin (Sn), Reel Packaged Documents: Note - Please disable browser pop-up blockers for documents on www.molex.com	Series image - Reference only
	Drawing (PDF) Product Specification PSX-44441-9999 (PDF)	EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No
		Halogen-Free Status Halogen-Free

Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any nonproduct compliance questions.

Search Parts in this Series 43375Series

Mates With

43178 Male Crimp Terminals

Use With

44441 Receptacle Housings

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below . Crimp Height Specifications are then contained in the Application Tooling Specification document. Global

Description Product # Mini-Mac™ Applicator 0638916000 Extraction Tool 0638132700 Manual Extraction Tool 0638130500 Terminator Die 0638405000 HAND CRIMP TOOL 0638117200

Crimp Quality Equipment

Molex also offers wire strippers, pull testers, shut-height gauges, micrometers and more

Click here for details

Product Literature (PDF)

Order Products:	
Part Detail: <u>(show all)</u>	
GeneralPhysicalMaterial InfoReferen	ce - Drawing Numbers
General	
Product Family	Crimp Terminals
Series	<u>43375</u>
Comments	Allows 44441 receptacle housings to meet UL 1950 finger proof standard.
Overview	<u>Sabre™</u>
Product Literature Order No	USA-113
Product Name	Sabre™
Physical	
Durability (mating cycles max)	25
Gender	Female
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Packaging Type	Reel
Plating min: Mating (µin)	20
Plating min: Mating (µm)	0.50
Plating min: Termination (µin)	20
Plating min: Termination (µm)	0.50
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	3.30mm (.130") max.
Wire Size AWG	14, 16
Wire Size mm ²	N/A
Material Info	
Reference - Drawing Numbers	
Product Specification	PSX-44441-9999, RPSX-44441-001
Sales Drawing	SD-43375-0001

Molex Connector Part Number - 0433750001

Feedback Privacy Legal Site Map Help

