THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.				REVISIONS				
			LTR	DE	ESCRIPTION	DATE	APPROVED	
© 2005, Projects Unlimited Inc. SPECIFICATIONS			-	RELEASED FROM	M ENGINEERING	10/11/06		
PARAMETERS	VALUES	UNITS						
RATED INPUT POWER	0.5	w						
MAX INPUT POWER	1	w						
IMPEDANCE	8±15%	ОНМ						
OUTPUT SPL @ 0.1W/0.1M (AT 0.8, 1.0, 1.2, 1.5, kHz)	91±3	dBA						
DISTORTION (MAX.)	5%	_						
RESONANT FREQUENCY	500±20%	Hz						
FREQUENCY RANGE	500 ~ 4500	Hz						
HOUSING MATERIAL	METAL	_						
CONE MATERIAL	MYLAR	_						
MAGNET MATERIAL	N38	-				7		
OPERATING TEMPERATURE	-20 ~ +60	·C			<b> −</b> −4.6±0	.3		
WEIGHT	12	grams		~ 7				
	-		$2\pm$	0.3				
					Ø15.3±	-0.3		
NOTES:	—ø36-		UNLESS OT DIMENSION: MILLIMETER ANGLES AF	THERWISE SPECIFIED: S ARE IN IS,TOLERANCES ARE ±0.5 AND RE ±3'.			Ohio	
1. ALL DIMENSIONS ARE IN MILLIMETERS.			AP	PROVALS DATE	SPF	AKER		
2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL			DRAWN	J.D. 10/06 B.R. 10/06	SIZE DRA	WING NO.		
WITHOUT NOTICE.		FILE NAME	APPROVED		A AS0360	8MR-5-F		
3. THIS PART IS ROHS 2002/95/EC COMPLIANT.		AS03608MR-5-R.DWG		R. W. 10,000	SCALE: N.T.S.	SHEET 1	of 1	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PUI Audio: AS03608MR-5-R