



**09 66 354 6511****D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 6.0 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level 2                 |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)

**09 66 354 5515****D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 5.7 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level S4                |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

09 66 354 5511

**D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 6.0 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level S4                |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

**09 66 354 6515****D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 5.7 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level 2                 |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

**09 66 354 7511****D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 6.0 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level 3                 |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)

**09 66 354 7515****D-Sub - S PCB connector**

Other applications

|                    |                                     |
|--------------------|-------------------------------------|
| gender             | female connector, straight          |
| Termination        | Press-In termination                |
| shell              | tinned metal shell                  |
| Number of contacts | 25 way                              |
| Flange heigh       | flange height 5.7 mm                |
| Board fixing       | with grounding press-in board locks |
| flange             | M 3                                 |
| Performance level  | Performance level 3                 |
| Material           | LCP                                 |

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)[DXF](#)