www.molexkits.com



| General Information | | | |
|---------------------------|--|--|--|
| Part Number: | 76650-0125 | | |
| Manufacturer: | Molex / Waldom | | |
| Title: | PicoBlade Connector Kit | | |
| Description: | Friction Lock Plug and Receptacle | | |
| Product Family: | PicoBlade™ | | |
| Certificates: | (Molex Parts within this kit) - UL and CSA | | |
| Country of Origin: | Kit assembled in U.S.A. | | |
| Specifications | | | |
| Design Configuration: | Wire-to-Wire | | |
| Pitch: | 1.25mm (.049") | | |
| Connector Type: | Plugs and Receptacles | | |
| Circuit Sizes: | 2, 3, 4, 6 and 10 | | |
| Current Rating: | 1 Amp | | |
| Voltage: | 125 Volts | | |
| Wire size: | 32-28 AWG | | |
| Product Highlights | | | |

1.25mm (.049") pitch PicoBlade[™] system is designed for high-density harness applications. PicoBlade provides the same 1.0 amperes of current as similar 2.00mm (.079") pitch systems, but in a more compact design. PicoBlade[™] is offered in wire-to-board and wire-to-wire options. The system saves about 45% of PCB space compared to typical 2.00mm wire-to-board systems. It is a single row system, available in 2 to 15 circuits, with both surface mount and through-hole headers.

| Features and Benefits | Applications |
|---|--|
| Reliable terminal for solid electrical connection Friction lock for good mating retention Polarizing features ensures proper mating orientation Two solder tabs for better connection to the PCB | Car Radios Process controls Cash dispensers Patient monitors Alarm systems Set top boxes DVD players |



Bill of Materials for Part No. 76650-0125

| Molex Part No. | Country of Origin | Description | Quantity in Kit |
|----------------|----------------------|---|--------------------|
| 51047-0200 | Japan | 1.25mm (.049") Pitch PicoBlade™ Plug , 2 Circuits | 10 |
| 51047-0300 | Japan | 1.25mm (.049") Pitch PicoBlade™ Plug, 3 Circuits | 10 |
| 51047-0400 | Japan | 1.25mm (.049") Pitch PicoBlade™ Plug, 4 Circuits | 10 |
| 51047-0600 | Japan | 1.25mm (.049") Pitch PicoBlade™ Plug, 6 Circuits | 10 |
| 51047-1000 | Japan | 1.25mm (.049") Pitch PicoBlade™ Plug, 10 Circuits | 10 |
| 51021-0200 | Japan | 1.25mm (.049") Pitch PicoBlade™ Receptacle, 2 Circuits | 10 |
| 51021-0300 | Japan | 1.25mm (.049") Pitch PicoBlade™ Receptacle, 3 Circuits | 10 |
| 51021-0400 | Japan | 1.25mm (.049") Pitch PicoBlade™ Receptacle, 4 Circuits | 10 |
| 51021-0600 | Japan | 1.25mm (.049") Pitch PicoBlade™ Receptacle, 6 Circuits | 10 |
| 51021-1000 | Japan | 1.25mm (.049") Pitch PicoBlade™ Receptacle, 10 Circuits | 10 |
| 50058-8000-C | Japan | PicoBlade™ Crimp Terminal, Female, 32-28 AWG | 100 |
| 50133-8100-C | Japan | PicoBlade™ Crimp Terminal, Male, 32-28 AWG | 100 |

Recommended Molex Tool(s) for Part No. 76650-0125*

| | Country | |
|----------------|-----------|-----------------|
| Molex Part No. | of Origin | Description |
| 63819-0400 * | Sweden | Hand Crimp Tool |
| 11-03-0043 * | USA | Extraction Tool |

*Tool(s) not included in kit. Tool(s) ordered separately.