

25-30 Watts

ALT ALT Dual

Total Power: 25 Watts for Single, 30Watts for Dual output
 Input Voltages: 48 V, 24V
 No. of Outputs: Single, Dual



Special Features

- 25W Single and 30W Dual output
- 2:1 Input range
- Open Frame package
- 1.6" X 2.0" X 0.48"
- Positive and Negative enable function
- Industry standard package

Environmental

Operating temperature
 -40°C to +55°C (ambient temperature)
 Storage temperature: -55°C to +125°C
 MTBF: 2 million hours (Bellcore TR332)

Safety

UL 1950 Recognized
 CSA CSA22.2 - 950
 VDE EN60950 Licensed

Electrical Specs

Input

Input range 48Vin:36-75 VDC
 24Vin: 18 - 36VDC
 Input Surge 48Vin: 100V / 100ms
 24Vin: 50V / 100ms
 Efficiency 87% @5.0V (Typical)

Control

Enable TTL compatible
 (positive & negative enable options)

Output

Regulation
 Line <0.2%
 Load <0.5%
 Ripple & Noise 75mV p-p for 3.3V and 5V of 48Vin
 100mV p-p for 3.3V and 5V of 24Vin
 150mV p-p for 12V and 15V
 150mV p-p for dual output
 Output voltage adjust range +/-10% of nominal output
 Transient Response 3% max deviation with 50% to 75% full load
 200 μ S (max) recovery for 48Vin
 300 μ S (max) recovery for 24Vin
 Overvoltage Protection 19V for 15V output
 16V for 12V output
 7V for 5V output
 5V for 3.3V output

Isolation

I/O isolation 1500VDC (Basic insulation)

AMERICAS

5810 Van Allen Way
 Carlsbad, CA 92008
 Telephone: 760-930-4600
 Facsimile: 760-930-0698

EUROPE

Astec House, Waterfront Business Park
 Merry Hill, Dudley
 West Midlands, DY5 1LX, UK
 Telephone: 44 (1384) 842-211
 Facsimile: 44 (1384) 843-355

ASIA

Units 2111-2116, Level 21
 Tower1, Metroplaza
 223, Hing Fong Road
 Fwai Fong, New Territories
 Hong Kong
 Telephone: 852-2437-9662
 Facsimile: 852-2402-4426




Ordering Information

ALT06/ALT-Dual


Input Voltage	Output Voltage	Efficiency	Model Number
48V	3.3V @ 6A	85% (Typ)	ALT06F48
48V	5.0V @ 5A	87% (Typ)	ALT05A48
48V	12V @ 2.1A	87% (Typ)	ALT02B48
48V	15V @ 1.67A	87% (Typ)	ALT01C48
24V	3.3V @ 6A	83% (Typ)	ALT06F24
24V	5.0V @ 5A	85% (Typ)	ALT05A24
Dual output			
48V	5.0V @ 3A	84% (Typ)	ALT03AA48
48V	12V @ 1.25A	87% (Typ)	ALT01BB48

Pin Assignments

Single Output



Dual Output



Astec Industry Standard