



## COUPLER Product Specification

**Model:** AY03L(Z)      **Rev:**      **Date:** 3/5/2007

**Customer:** SIRENZA MICRODEVICES, INC.

**Operating Temperature Range:** ( -40 ° to 85 ° C)

**Pb** WEEE and RoHS Compliant

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	3400		3500	MHz	X	
Coupling Value -		3		dB	X	
Insertion Loss -	0	0.1	0.3	dB	X	
Amplitude Balance -	-0.3	0	0.3	dB	X	
Phase Balance -	85	90	95	degrees	X	
Return Loss -			-19.1	dB	X	
Output Isolation -	21			dB	X	
Power Handling -			60	Watts		Average Power CW

### Package Information

Package Type:	L (0.56 x 0.35 x 0.075 inches)	Drawing Number:	SLG003
---------------	--------------------------------	-----------------	--------

### Comments

**X** Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.

Page 1 of 1