

181-00249



**Article Number:** 181-00249

**Solid Wall Wiring Duct, 2" X 5", Non-Adhesive, PVC, White, 30ft/Carton**



## Base Data

**Local Order Number** 181-00249

**Type** SD2X5

**Color** White (WH)

- Features and Benefits**
- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
  - Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
  - Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, 2" X5", Non-Adhesive, PVC, White, 30ft/Carton

## Product Dimensions

**Length L (imperial)** 6.0 ft

**Length L (metric)** 1.83 m

**Width W (imperial)** 2.0 "

**Width W (metric)** 50.8 mm

**Width W2 (imperial)** 2.0 "

**Width W2 (metric)** 50.8 mm

**Height H (imperial)** 5.0 "

**Height H (metric)** 127.0 mm

**Mounting Hole Centers (imperial)** 4.0 "

**Mounting Hole Centers (metric)** 101.60 mm

## Logistics and Packaging

**Package Quantity** 30

## Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122 °F (+50 °C)

**ROHS Conformity** Yes

**Certification / Specification** CSA  
UL

UL Recognized (US) Yes

---

© HellemanTyton 2014