

1

2

3

4

5




6

7

A

4,98

6,47




NOTES:

- 1. Insulation: Glass Filled PBT, UL94V-0, Color Black/Red/Blue
- 2. Contact : Phosphor Bronze
- 3. Current Rating: 3A Max
- 4. Dielectric Voltage: 1000V rms / 1 minute
- 5. Insulation Resistance: 1000M ohm Min.
- 6. Contact Resistance: 30m ohm Max.
- 7. Operating and Storage Temperature: -40°C ~ +105°C
- 8. Mating Cycles: 10 Min.

AKSCT/x x

- ④ Contact Area Plating:
  - G: Gold Flash
  - Z: Tinned
- ② Insulation color:
  - BLACK: Black
  - BLUE: Blue
  - RED: Red

D



E

F

ROHS compliant

Unit:mm

G

H

Scale	Free
TOLERANCE	
.X	±0.38
.XX	±0.25
.XXX	±0.13
DIM	TOL
X. °	±1°
Angle	TOL
UNIT	mm

④	②	③	①	Id.	Modification	Date	Name
Update	Update	Update	Drawn				
21.11.2012	27.07.2009	10.04.2002					
Any	Rate	Hellwig					

Date	Name
10.04.2002	Hellwig
07.06.2013	Winnie



Customer-No.

ASSMANN WSW-No.

AKSCT/G X  
AKSCT/Z X

Drawing-No.

ASS 0591 CO

rev04

Replace

SHEET

G

F

E

D

C

B

A

1

2

3

4

5

6

7

H