ACLD Screw Termination Boards

Features

General

- Low-cost universal screw termination boards
- Blank pads accommodate applications such as break detection, low-pass filter, current shunt and voltage attenuator on ACLD-9881-01, ACLD-9178-01, ACLD-9188-01, ACLD-9138-01, and ACLD-8125-01
- Table-top mounting using nylon standoffs

ACLD-9881-01(1)

General-Purpose Termination Board with One 37-pin D-sub Connector for PCI-9113A and ACL-8113A

- For use with PCI-9113A and ACL-8113
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:
 - · ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
- Dimensions: 222 mm x 105 mm

ACLD-9188-01(1)

General-Purpose Termination Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector

- Onboard 20-pin ribbon male connector x 2
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cable:
 - ACL-10120-1: 20-Pin Flat Cable, 1 M
- Dimensions: 222 mm x 114 mm

ACLD-9138-01(1)

General-Purpose Termination Board with one 37-pin D-sub Connector

- Onboard 37-pin D-sub female connector
- Blank RC circuits for analog input boards
- Reliable screw clamp termination blocks
- Mating Cable:
 - ACL-10237-1: 37-Pin D-sub male/male flat Cable, 1 M
- Dimensions: 103 mm x 114 mm

ACLD-9137-01/ACLD-9137F-01

General-Purpose Termination Board with one 37-pin D-sub Connector

- ACLD-9137: onboard 37-pin D-sub male connector
- ACLD- 9137F: onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
 - ACL-10137-1MF: 37-Pin D-sub male/female Cable, 1 M (ACLD-9137-01)
- Dimensions: 124 mm x 72 mm

ACLD-8125-01(1)

Termination Board with one 37-pin D-sub Connector and One Cold Junction Temperature Sensor

- One onboard temperature sensor for cold-junction compensation ■ Jumper configurable sensor outputs in either DI or SE mode
- Onboard calibration for the temperature sensor
- Onboard 37-pin D-sub female connector
- Reliable screw clamp termination blocks
- Mating Cables:
- - ACL-10137-1MM: 37-Pin D-sub male/male Cable, 1 M
- Dimensions: 168 mm x 114 mm

TB-6201-01/6221-01/6231-01(1)

General-Purpose/Multiplexer/Matrix switch termination board with one 62-pin D-sub connector

- Termination board for PXI-7901/7921/7931
- Onboard connector type: 62-pin D-sub female
- Mating Cable:
 ACL-10262: 62-Pin D-sub male/female cable
- Reliable screw clamp termination blocks
- Dimensions: 105.81 mm x 2.30 mm

Note: (1) Cables are not included.

ACLD-9881-01



ACLD-9188-01



ACLD-9138-01




ACLD-9137-01/ACLD-9137F-01



ACLD-8125-01



TR-6201-01



Ordering Information

■ ACLD-9881-01

General-Purpose Termination Board with one 37-pin D-sub Connector

- ACI D-9188-01
- General-Purpose Termination Board with Two 20-pin Ribbon Connectors and One 37-pin D-sub Connector
- ACLD-9138-01
- General-Purpose Termination Board with one 37-pin D-sub Connector
- ACLD-9137-01
- General-Purpose Termination Board with one 37-pin D-sub Male Connector
- ACLD-9137F-01

General-Purpose Termination Board with one 37-pin D-sub Female Connector

■ ACLD-8125-01

Termination Board with one 37-pin D-sub Connector and One Cold Junction Temperature Sensor

TB-6201-01

General-Purpose Switch Termination Board with one 62-Pin D-Sub Female Connector

■ TB-6221-01

Multiplexer Switch Termination Board with one 62-Pin D-Sub Female Connector

■ TB-6231-01

Matrix Switch Termination Board with one 62-Pin D-Sub Female Connector



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ADLINK Technology:

ACLD-9188-01 ACLD-9137F-01 ACLD-8125-01 ACLD-9137-01 ACLD-9881-01 ACLD-9138-01