


Feed-through terminals mit TS 32 Fuß

SAKD 2.5 N


Compact design



SAK 2.5



Approvals

Dimensions (W x L x H with TS 32 ) in mm

Rated data

Rated voltage	V
Rated current	A
Rated cross-connection	mm ² /AWG
Rated impulse voltage/	kV
Pollution severity	

Ordering data

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	SAKD 2.5 N	0215560000
blue PA	SAKD 2.5 N	0021558000
orange PA	SAKD 2.5 N	
green-yellow PA		

10-channel terminal block with printed marker DEK 5 1-9 PA

10-channel block with unprinted marker DEK 5 neutral PA

End plate

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	AP (1.5)	0150960000
blue PA	AP (1.5)	0191880000

Partition / Small partition

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	TW (1.5)	0191860000
blue PA	TW (1.5)	0191880000
HP	TW (1.5)	0307500000
TSch 3	TSch 3	0366860000

Cross-connection

Version	Part No.	Qty.
2-pole	Q 2	0367800000
3-pole	Q 3	0367900000
4-pole	Q 4	0368000000
10-pole	Q 10	0368100000

Clampable conductors

Version	Part No.	Qty.
solid H07V-U	mm ²	0.5...4
stranded H07V-R	mm ²	0.5...2.5
flexible H07V-K	mm ²	0.5...4
flexible H07V-K und AEH DIN 46 228/1		
with / without Plastic insul. collar	mm ²	0.5...2.5
Gauge pin acc. to 60 947-1	Size	A 2
Cont. current of terminal for conductor size		30 A/4 mm ²
Cont. current of Cross-connection WQV/ZQV 2...5-pole	A	24
Cont. current of Cross-connection WQV/ZQV 6...10-pole	A	24

Further technical data

Version	Part No.	Qty.
Tightening torque range	Nm	0.4...0.6
Insulation stripping length/clamping screw/screwdriver blademm		10/M 2.5/3.5 x 0.6

Accessories

Version	Part No.	Qty.
Cover		
Screw für Cover		
Cross-connection link		
Connection sleeve		
Fixing srew		
Marking tags DEK	DEK 5	

Approvals

5 x 32.5 x 43.5

Rated data

IEC 60 947-7-1	UL	CSA
500	300	300
24	20	20
2.5	28...12	22...12
6		
3		

Ordering data

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	SAKD 2.5 N	0215560000
blue PA	SAKD 2.5 N	0021558000
orange PA	SAKD 2.5 N	
green-yellow PA		

10-channel terminal block with printed marker DEK 5 1-9 PA

10-channel block with unprinted marker DEK 5 neutral PA

End plate

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	AP (1.5)	0150960000
blue PA	AP (1.5)	0191880000

Partition / Small partition

Version	Part No.	Qty.
KrG		
blue KrG		
KrS		
PA	TW (1.5)	0191860000
blue PA	TW (1.5)	0191880000
HP	TW (1.5)	0307500000
TSch 3	TSch 3	0366860000

Cross-connection

Version	Part No.	Qty.
2-pole	Q 2	0367800000
3-pole	Q 3	0367900000
4-pole	Q 4	0368000000
10-pole	Q 10	0368100000

Clampable conductors

Version	Part No.	Qty.
solid H07V-U	mm ²	0.5...4
stranded H07V-R	mm ²	0.5...2.5
flexible H07V-K	mm ²	0.5...4
flexible H07V-K und AEH DIN 46 228/1		
with / without Plastic insul. collar	mm ²	0.5...2.5
Gauge pin acc. to 60 947-1	Size	A 2
Cont. current of terminal for conductor size		30 A/4 mm ²
Cont. current of Cross-connection WQV/ZQV 2...5-pole	A	24
Cont. current of Cross-connection WQV/ZQV 6...10-pole	A	24

Further technical data

Version	Part No.	Qty.
Tightening torque range	Nm	0.4...0.6
Insulation stripping length/clamping screw/screwdriver blademm		10/M 2.5/3.5 x 0.6

Accessories

Version	Part No.	Qty.
Cover		
Screw für Cover		
Cross-connection link		
Connection sleeve		
Fixing srew		
Marking tags DEK	DEK 5	

Approvals

6 x 36.5 x 46.5

Rated data

IEC 60 947-7-1	UL	CSA
800	600	600
24	20	25
2.5 ³⁾	22...12	26...10
8		
3		

Ordering data

Type	Part No.	Qty.
SAK 2.5	0279620000	100
SAK 2.5	0279670000	100
SAK 2.5	0279630000	100
SAK 2.5	0279660000 ¹⁾²⁾	100
SAK 2.5	0279680000 ¹⁾²⁾	100
SAK 2.5	1326360000 ¹⁾²⁾	100

10-channel terminal block with printed marker DEK 5 1-9 PA

10-channel block with unprinted marker DEK 5 neutral PA

End plate

Type	Part No.	Qty.
SAK 2.5/10	0322560000 ¹⁾²⁾	10
SAK 2.5/10	0322860000 ¹⁾²⁾	10
AP (1.5)	0279520000	20
AP (1.5)	0279570000	20
AP (1.5)	0279530000	20
AP (1.5)	0279560000	20
AP (1.5)	0279580000	20

Partition / Small partition

Type	Part No.	Qty.
TW (2.5)	0302820000	20
TW (2.5)	0302870000	20
TW (2.5)	0302830000	20
TW (1.5)	0302860000	20
TW (1.5)	0302880000	20
TW (1.0)	0297100000	20
TSch 1	0319160000	100

Cross-connection

Type	Part No.	Qty.
Q 2	0337000000	50
Q 3	0337100000	50
Q 4	0337200000	50
Q 10	0368700000	20

Clampable conductors

Version	Part No.	Qty.
solid H07V-U	mm ²	0.5...6
stranded H07V-R	mm ²	0.5...2.5
flexible H07V-K	mm ²	0.5...4
flexible H07V-K und AEH DIN 46 228/1		
with / without Plastic insul. collar	mm ²	0.5...2.5/4 ³⁾
Gauge pin acc. to 60 947-1	Size	A 3
Cont. current of terminal for conductor size		32 A/4 mm ²
Cont. current of Cross-connection WQV/ZQV 2...5-pole	A	24
Cont. current of Cross-connection WQV/ZQV 6...10-pole	A	24

Further technical data

Version	Part No.	Qty.
Tightening torque range	Nm	0.4...0.6
Insulation stripping length/clamping screw/screwdriver blademm		10/M 2.5/3.5 x 0.6

Accessories

Type	Part No.	Qty.
AD 4	0303400000	50
BSK M 3 x 22	0128900000	100
DEK 6		

¹⁾ Finger-safe cross-connection with ADP 4 cover profiles (see main catalogue)

²⁾ Not suitable for locking pin SST 3

³⁾ Part No. 0279660000, 0279680000, 41 A at 6 mm²